



DIMMABLE
5% - 100%

LED Disk Light with Selectable Color

soft white - 3000K bright white - 4000K daylight - 5000K




Performance
Excellent color rendering (90 CRI)




DUAL INSTALLATION

4" J-box Flush Mount Accessories included



- Attach mounting bracket to J-box
- Click downlight into mounting bracket



Mounting Bracket

J-Box Screws



Wire Nuts

LED Adapter



15w 6 inch Ceiling Downlight Surface Mounted Led Disk Light

Description

ETL-listed LED disk light is a downlight with High performing white light and optimized for new construction and retrofit applications. Multiple installation options for both recessed and surface mount applications. Installation is done quickly and easily in most standard five-inch and six-inch Insulated Ceiling housings, It can also be surface mounted to standard 4-inch J-Box or using specially designed Connector Box.

Performance

Excellent color rendering (90 CRI), and color temperatures of 2700K,3000K ,4000K and 5000K.

Warranty

Comes with 5 years product warranty for customer's rights and benefits, satisfaction guarantee.

Applications

Ideal for applications such as Healthcare, Hospitality, Office, Residential, Retail.

Hassle-Free Installation

Installation is quick and easy in most recessed housings with torsion springs and friction blades for your option according to the housing you are using. The E26 adapter can fit directly into your existing bulb socket. For surface mount applications, we provide you with an orange adapter with pre-stripped wire which is used to wire into the junction box in the ceiling.

Notice: Suitable for damp locations. Turn off power before installation.

| Wattage | 10W | 15W |
|--------------------|-------------------------------|-------------------------------|
| Lumen | 700lm | 1200lm |
| Equivalent | 65W | 100/120W |
| Voltage | AC120V (-60Hz) | AC120V (60Hz) |
| Color Temp | 2700K-3000K-3500K-4000K-5000K | 2700K-3000K-3500K-4000K-5000K |
| CRI | >90 | >90 |
| Power Factor | >0.9 | >0.9 |
| Dimmable | Triac dimmable 5%~100% | Triac dimmable 5%~100% |
| Material | Aluminum | Aluminum |
| Lifespan | 50,000 Hours | 50,000 Hours |
| Finish | White | White |
| Base | E26/TP24 | E26/TP24 |
| IP & IK Rating | IP44 | IP44 |
| Warranty | 5 Years | 5 Years |
| Wet Location Rated | Yes | Yes |
| Installation | Surface / Recessed | Surface / Recessed |

