

LED EXIT REMOTE HEAD COMBO

Thermoplastic LED Exit Combo



FEATURES & SPECIFICATIONS

Construction

- Injection-molded thermoplastic ABS housing
UL-94V-0 flame rating - Flame Retardant, high temperature, thermoplastic hosing
- Universal design includes two faceplates, one backplate, and mounting canopy
- All configurations include field-selectable directional chevrons
- Standard finish: White

Optical System

- High intensity red LEDs.
- Dual battery with remote capabilities
- Fully-illuminated 6" characters with 3/4" stroke
- LED Heads - 1.2 Watt per lamp head compatible with 9.6V
- Double Face Configuration

Electrical

- Standard Universal Voltage - 120/277VAC Dual Voltage Operation
- LED Indicator Light & Push Button Test Switch
- Power Draw (W): 2.4
- Test button to provide manual verification of the transfer circuit and emergency lamps
- Compatible with up to two optional remote lamp heads

Battery

- Maintenance free AA Type, NiCad Battery
- Operating Temperatures 0°C to 40°C (32°F to 104°F)

Installation

- Easy snap together design for effortless installation

- Includes mounting canopy for wall and ceiling mount applications

Warranty

- 5 year warranty on all electronics and housing
- Separate 2 year pro-rated warranty on the battery

Listings

- UL 924
- UL listed for damp locations (20 °C -40 °C)
- 90 minute emergency run time, 24 hour recharge time

ORDERING GUIDE

TYPICAL ORDER EXAMPLE: **BRT-EM-CMB-RH-RL-WH-UNV**

Prefix	Letter Color	# of Faces	Housing Color	Lamp Heads	Options
BRT-EM-EXT Thermoplastic Exit Combo	R - Red	U - Universal (includes two face plates, back plate, and mounting canopy)	WH - White	RH - 1.2 Watt LED Heads	

PRODUCT DIMENSIONS

