




EAN Code left hinge door: 3543290003841



EAN Code right hinge door: 3543290003650

Configuration



Bottles capacity with the standard configuration; 6 storing shelves : **199 Bottles***

CONFIGURATION	Storing shelf	Sliding shelf	Capacity*
Optimum Configuration (100% sliding shelves)	-	9	163
Standard Configuration	3	3	199

Oxygen



Gamme :	Oxygen
Fonction :	Ageing (I-temperature)
Model right hinge door :	OXG3T199NPD
Model left hinge door :	OXG3T199NPG
Equipement :	6 shelves (3 storing shelves and 3 sliding shelves) and 2 compartments
Capacité :	199 Bottles*



Constant and reliable temperature thanks to the wine cabinet insulation, the controller and the aluminium walls.



Humidity rate between 65% and 80% ensuring by our product design, the cooling and venting system,



The natural venting system of our wine cabinets ensures constant air renewal within the wine cabinet.



Ideal protection against UV rays thanks to our solid door with highly effective UV filter.



No vibration thanks to the slow-cycles compressor fixed on silent blocs + evaporator flooded in the high density polyurethane foam.

General Features

Dimensions H x W x D (mm):	1825 x 680 x 725**	Weight cabinet empty (kg) :	79
Dimensions in pack (mm) :	1950 x 720 x 760	Weight equipped cabinet (kg) :	94,6
Colors :	Black	Weight in pack (kg) :	110,6
Door:	Solid door silver frame	Useful volume (L) :	446

Equipment & Accessories

Equipment

- Solid black door with silver frame, stainless steel handle
- Lock
- Left or right opening
- 2 adjustable feet
- Labels for the bottles identification
- 2 compartments in wood

Accessories

Universal shelves: AOHUI

Code EAN : 3543290002783

Weight : 2,6 kg

Bottles capacity per level : 12*

Material : Solid beech wood.

Modular system : you can choose the shelf configuration :



Sliding shelf
« 12 bottles »



Presentation shelf
« 6+22 bottles »



Storing shelf
« 72 bottles »

The label holder allows you to identify your bottle quickly and easily



Suitable to store all types of bottles



Technical features

Control Panel

- Electronic regulation from 10°C to 14°C for the middle part of the cabinet. From 15°C to 20°C for the highest part of the cabinet. The temperature of the lowest part of the wine cabinet is defined by the temperature setting of the middle part.
- Inner electronic display, Red Leds screen
- Visual alarm for the temperature fault
- Temperature display
- Automatic Winter function

Performances

Cold production :	Static cooling
Hot production :	Heating element
Humidity:	Ensure by the thermodynamical pump system
Winter function:	Automatic
Gaz uses :	R600a
Recommended temperature range :	From 12°C to 30 °C
Inner material:	Aluminium
Insulation type:	PU foam
Acoustic emissions (db(A)):	37
Acoustical emission class :	C
Consumption (kWh/year) :	150
Energy efficiency rating :	F

* Traditional Bordeaux bottles

** With the rear stop, without the handle