




EAN Code : 3543290003605

Configuration



Bottles ²capacity with the standard configuration; 4 storing shelves :
182 Bottles*

CONFIGURATION	Storing shelf	Sliding shelf	Capacity*
Optimum Configuration (100% sliding shelves)	-	10	141
Mixt Configuration	2	1	177
Standard Configuration	3	0	182

Oxygen



Gamme :	Oxygen
Fonction :	Ageing (I-temperature)
Reference :	OXMITI82NPD
Equipement :	3 storing shelves
Capacité :	182 Bottles*



Homogenous constant and reliable temperature thanks to the wine cabinet insulation, the controller and the aluminium walls.



Humidity rate between 65% and 80% ensuring by our product design, the cooling and venting system,



The natural venting system of our wine cabinets ensures constant air renewal within the wine cabinet.



Ideal protection against UV rays thanks to our glass door with double pan reinforced with gaz argon to filter up to 97% of the UV rays.



No vibration thanks to the slow-cycles compressor fixed on silentblocs + evaporator flooded in the high density polyurethane foam.

General Features

Dimensions H x W x D (mm):	1480 x 680 x 720**	Weight cabinet empty (kg) :	74
Dimensions in pack (mm) :	1605 x 720 x 760	Weight equipped cabinet (kg) :	81,8
Colors :	Black	Weight in pack (kg) :	96,8
Door:	Glass door silver frame	Useful volume (L) :	360

Equipment & Accessories

Equipment

- Glass door with silver frame, integrated handle in the glass frame.
- Glass door with double pan reinforced with gaz argon to filter up to 97% of the UV rays.
- Lock
- Reversible door
- 2 adjustable feet
- Labels for the bottles identification

Accessories

Universal shelves: AOHUI

Code EAN : 3543290002783

Weight : 2,6 kg

Bottles capacity per level : 12*

Material : Solid beech wood.

Modular system : you can choose the shelf configuration :



Sliding shelf
« 12 bottles »

The label holder allows you to identify your bottle quickly and easily



Presentation shelf
« 6+22 bottles »



Storing shelf
« 72 bottles »

Suitable to store all types of bottles



Technical features

Control Panel

- Electronic regulation from 9°C to 15°C; one identical temperature inside the wine cabinet
- Inner electronic display, Red Leds screen
- Visual alarm for the temperature fault
- Temperature display
- Automatic Winter function

Performances

Cold production :	Static cooling
Hot production :	Heating element
Humidity:	Ensure by the thermodynamical pump system
Winter function:	Automatic
Gaz uses :	R600a
Recommended temperature range :	From 0°C to 30 °C
Inner material:	Aluminium
Insulation type:	PU foam
Acoustic emissions (db(A)):	37
Acoustical emission class :	C
Consumption (kWh/year) :	154
Energy efficiency rating :	G

* Traditional Bordeaux bottles

** With the rear stop, without the handle