




EAN Code : 3543290003612

Configuration



Bottles capacity with the standard configuration; 4 storing shelves :
182 Bottles*

CONFIGURATION	Storing shelf	Sliding shelf	Capacity*
Optimum Configuration (100% sliding shelves)	-	9	122
Mixt Configuration	2	1	177
Standard Configuration	3	0	182

Oxygen



Gamme :	Oxygen
Fonction :	Ageing (I-temperature)
Reference :	OXMITI82NPD
Equipement :	3 storing shelves
Capacité :	182 Bottles*

- Homogenous constant and reliable temperature thanks to the wine cabinet insulation, the controller and the aluminium walls.
- Humidity rate between 65% and 80% ensuring by our product design, the cooling and venting system,
- The natural venting system of our wine cabinets ensures constant air renewal within the wine cabinet.
- Ideal protection against UV rays thanks to our solid door with highly effective UV filter.
- No vibration thanks to the slow-cycles compressor fixed on silentblocs + evaporator flooded in the high density polyurethane foam.

General Features

Dimensions H x W x D (mm):	1480 x 680 x 725**	Weight cabinet empty (kg) :	63
Dimensions in pack (mm) :	1605 x 720 x 760	Weight equipped cabinet (kg) :	70,8
Colors :	Black	Weight in pack (kg) :	85,8
Door:	Solid door silver frame	Useful volume (L) :	360

Equipment & Accessories

Equipment

- Black solid door with silver frame, stainless steel handle black or silver color.
- Lock
- 2 adjustable feet
- Labels for the bottles identification

Accessories

Universal shelves: AOHUI

Code EAN : 3543290002783

Weight : 2,6 kg

Bottles capacity per level : 12*

Material : Solid beech wood.

Modular system : you can choose the shelf configuration :



Sliding shelf
« 12 bottles »

The label holder allows you to identify your bottle quickly and easily



Presentation shelf
« 6+22 bottles »



Suitable to store all types of bottles



Storing shelf
« 72 bottles »



Technical features

Control Panel

- Electronic regulation from 9°C to 15°C; one identical temperature inside the wine cabinet
- Inner electronic display, Red Leds screen
- Visual alarm for the temperature fault
- Temperature display
- Automatic Winter function

Performances

Cold production :	Static cooling
Hot production :	Heating element
Humidity:	Ensure by the thermodynamical pump system
Winter function:	Automatic
Gaz uses :	R600a
Recommended temperature range :	From 0°C to 35 °C
Inner material:	Aluminium
Insulation type:	PU foam
Acoustic emissions (db(A)):	37
Acoustical emission class :	C
Consumption (kWh/year) :	125
Energy efficiency rating :	F

* Traditional Bordeaux bottles

** With the rear stop, without the handle