

A 1 temperature cabinet adjustable from 6°C to 18° to mature your wines in the best possible conditions.



Code : ER1TGV3

Internal layout : SHELVES

Storage shelf : AXUHT

Weight: 1,8 kg

Dimensions (WxDxH): 535 x 525 x 28 mm

Type of structure: slats

Number of bottles: up to 77

Material: Solid Beechwood coated with an ecological water varnish.



« Storage »
77 Bottles

Sliding shelf : ACUPHT

Weight: 4 kg

Dimensions (WxDxH): 533x529x27mm

Type of structure: table

Number of bottles: up to 12

Material: Steel and PS shock



« Sliding »
12 Bottles

| Pack Type (sliding + storage shelves) | Pack Sliding | Storage Capacity |
|---------------------------------------|--------------|------------------|
| 215 | 182 | 234 |
| 3 storage 3 sliding | 14 sliding | 3 storage |

* Maximum capacity

** Empty wine cabinet

*** Traditional Bordeaux bottles

**** Whit the rear stop, without the handle

Range : **PRESTIGE**
Model : **Ermitage Full Glass door**
Function : **Ageing**
Capacity* : **234 Bottles*****

TECHNICAL BENEFITS

Combine technology/ performances and protection of the environment.

New Full Glass door using two panes reinforced with argon gas that guarantee better isolation and better protection against UV rays.

A constant temperature thanks to a double hot-cold regulation.

Suitable hygrometry thanks to a warmer and wetter air supply.

Air circulation ensured by the principle of thermodynamic pump.

No vibration thanks to the slow-cycles compressor fixed on silent blocs.

Storage or sliding shelves. One shelf for all kind of bottles.

GENERAL FEATURES

| | |
|--|------------------|
| Gross weight, packaged(Kg) | 98 |
| Net weight (Kg)** | 90 |
| Dimensions in packaging H x W x D (mm) | 1910x733x768 |
| Dimensions H x W x D(mm) | 1825x680x720**** |

| | |
|--|------|
| Energy efficiency rating | G |
| Acoustic emissions (dB(A)) | 37 |
| Acoustic emissions class | C |
| Consumption per 24h (KWh) | 0,52 |
| Annual energy consumption (kWh/year) | 190 |
| Ambient temperature operating limit (°C) | 0-30 |
| Useful volume (L) | 461 |

- ✓ Electronic regulation. (1T = 6-18°C).
- ✓ Internal temperature display on the digitalscreen.
- ✓ Low energy consumption (59mm PU foam).
- ✓ Visual alarms : Temperature sensor defect, Temperature level (when too high or too low), Hygrometry (when too low, for 1 temp. only).
- ✓ Lighting system: 3 options: Permanent lighting, Lighting when door opening, No lighting.
- ✓ Double Hot/ Cold circuit > Automatic « Winter function».
- ✓ Hygrometry ensured by the principle of thermodynamic pump.
- ✓ Anti-UV protection , 97% of UV rays are filtrated
- ✓ 2 adjustable feet (front).
- ✓ Lock system.
- ✓ Storage grid in the lower part.
- ✓ Black stainless steel handle. Removable.
- ✓ Reversible door
- ✓ Inner material: Stucco Aluminum.
- ✓ Compressor - R600a Gas.
- ✓ Colors : Black or Tobacco.