

# DATA SHEET SWISSCAVE CLB-160

## Technical Data

Exterior	
Casing	Black coated steel
Door glazing	Fully glazed UV-resistant, gas-filled, with low energy panes equipped glass door (double glazed)
Door frame	Filigree edging made of black anodised, brushed aluminium
Door handle	Anodised, brushed aluminium (rectangular)
Door lock	Yes
Door hinge	Right
Door hinge convertible as option (right to left)	Yes
Product dimensions without door handle (H/W/D)	820 x 595 x 620 mm
Packaging dimensions (H/W/D)	865 x 650 x 655 mm
Interior	
Temperature zones	1
Lighting	all around illumination white, blue, amber (adjustable)
Lighting on/off switch	Yes
Number of shelves total	3
Shelf material	Cedar wood
Telescopic shelves on extendable steel ball bearings	Full extension shelves (80%)
Inside casing	Black PUR
Scope of functions	
Optimal usage	Long-term storage and aging
User interface	2 digital displays (set and actual temp.)
Active carbon filters (ensuring optimal air quality)	Yes
Compressor	Embraco Fullmotion (speed-controlled)
Coolant	R600a (environment friendly)
Vibrationfree implementation	Yes
Cooling system	Combined fan and convection cooling
Temperatur Memory Function (Power failure)	Yes
Condensation water container	Yes
Heating	Yes (integrated powerful winter function)
Acoustic temperature alarm	Yes
Acoustic door alarm	Yes
Feet adjustable to compensate uneven floors	Yes

Performance data	
Humidity	Recommendation 50-70%
Actively managed humidity (adjustment range 60-80%)	Yes
Climate classification	SN-T
Volume	127 l
Noise level	37 dB(A) <b>sound-absorbing recommendation</b>
Temperature range	5°C - 20°C
General Information	
Cooler shape	Freestanding or built-in with shadow gap
Maintenance contract (warranty extension)	<b>Recommended</b>
Transport weight	54 kg
Net weight	50 kg
Power consumption per day	0.285 kWh (ca.)
Voltage	220 V / 50 Hz
Cable length	2m

