

LED FLOOD LIGHTS



Unit 2/1 Ismail Street
Wangara 6065
Western Australia

ABN: 14 292 378 514
1300 880 436

- Powder coated die-cast aluminium construction
- Tempered clear glass diffuser
- Inbuilt driver for direct connection to 240V supply
- Prewired to 1.5m flex & plug
- Weather resistant IP65



| Product Code | Voltage | Wattage (W) | Power Factor | Luminous Flux (Lm) | Plug & flex | Dimmable | Colour temp | IP Rating |
|---------------|---------|-------------|--------------|--------------------|-------------|----------|-------------|-----------|
| B0701-03-10W | 240V AC | 10W | 0.92 | 1000 | YES | No | 5500 (CW) | 65 |
| B0701-03-20W | 240V AC | 20W | 0.92 | 2000 | YES | No | 5500 (CW) | 65 |
| B0701-03-30W | 240V AC | 30W | 0.92 | 3000 | YES | NO | 5500 (CW) | 65 |
| B0701-03-50W | 240V AC | 50W | 0.92 | 5000 | YES | No | 5500 (CW) | 65 |
| B0701-03-100W | 240V AC | 100W | 0.92 | 10000 | YES | No | 5500 (CW) | 65 |
| B0701-03-150W | 240V AC | 150W | 0.92 | 15000 | YES | No | 5500 (CW) | 65 |
| B0701-03-200W | 240V AC | 200W | 0.92 | 20000 | YES | No | 5500 (CW) | 65 |

*Other sizes from 300-1000W (150lms/W) also available, pre-order is required

