

## Electronic

Additional info for **zcM1100** & **zcM2200**

- Photocell actuated feed & cut or push-button feed & cut
- Guillotined cut for a straight edge piece of tape
- LED Digital length adjustment
- Manual override of preset lengths
- Blades good for up to 200,000 cuts (dependent on type of material)
- Steel frame for durability
- Cabinet made from flame retardant antistatic composite (auto ignition of 896° F/ 480°C)
- Comes with a 3-in-1 core (1" (25mm), 1.4" (35mm), 3" (76mm))
- Adjustable pressure roller for different thicknesses of tape
- Accuracy of tape length is +/- .04" (1mm) (dependent on type of material)
- Many available accessories fit this machine. See Accessories section.
- All 230V machines are CE Certified

### Suggested accessory:

zcM1000P026

External Reel Stand –  
Max. OD 9.45" (240mm)

See Accessories Page 30



For the **zcM1100** and the **zcM2200**, the **B, K, T** and **NM** modifications are now available.

For 230V machines, please add "-2" to the end of the model number. (Example: **zcM1100-2**)

### zcM1100

#### Electronic Tape Dispenser with Safety Guard Cutting Head

- Safety guard system prevents activation of cutter when foreign objects are present (fingers, tools, etc.)
- Ideal for medium to high production of repetitive taping for industrial applications
- Program a defined length and automatically advance and cut tape
- Accepts tape widths from .28" to 2" (7 to 51mm)
- Cuts tape lengths from 1.2" to 39" (30 to 999mm)
- Made in Japan



Safety Mechanism

While it is not recommended to place foreign objects in the cutting area, the **zcM1100** and **zcM2200** are inoperable when the cutting head is obstructed.

### zcM2200

#### Electronic Tape Dispenser with Safety Guard Cutting Head and 3 Programmable Tape Lengths

- Safety guard system prevents activation of cutter when foreign objects are present (fingers, tools, etc.)
- Program 3 defined lengths and automatically advance and cut tape
- Ideal for medium to high production of repetitive taping for industrial applications
- Two operating modes: on demand lengths or consecutive
- Accepts tape widths from .28" to 2" (7 to 51mm)
- Cuts tape lengths from 1.2" to 39" (30 to 999mm)
- Made in Japan



MODEL #	Tape Width	Programmable Memory	Cut Length	Max. Outside Dia. of Roll	3-in-1 Core Holder	Accuracy of Cut**	Length Setting	Weight	Dimensions
<b>zcM1100</b>	.28 to 2.0" (7 to 51mm)	1	1.2 to 39" (30 to 999mm)	7" (178mm)	1", 1.4", 3" (25, 35, 76mm)	+/- .04" (1mm)	digital (LED)	6 lbs (2.72 kg)	9.8"(L) x 5.4"(W) x 6.2"(H) 25cm(L) x 14cm(W) x 16cm(H)
<b>zcM2200</b>	.28 to 2.0" (7 to 51mm)	3	1.2 to 39" (30 to 999mm)	7" (178mm)	1", 1.4" 3" (25, 35, 76mm)	+/- .04" (1mm)	digital (LED)	6 lbs (2.72 kg)	9.8"(L) x 5.4"(W) x 6.2"(H) 29cm(L) x 14cm(W) x 16cm(H)

Electrical requirements: 117V 50/60Hz, <1 amp (230V 50/60Hz CE available) \*\* dependent on material