

FULL METAL JACKET PAINT PROTECTION

MATERIAL SAFETY DATA SHEET

IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: Full Metal Jacket Paint Protection

Recommended Use: Paint Protection

Supplier: SPQR Australia P/L

Street Address: 37 Production Drive

Campbellfield, Victoria

Australia 3061

Phone Number: +61 3 9357 5503

Email: info@finalinspection.com.au

COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Nature:	Liquid mixture	
Chemical Name	CAS Number	Content
Alkoxysilane	proprietary	<10%
Siloxane	proprietary	<50%
Carrier Oil	proprietary	<40%
Copolymer Surfactant	proprietary	<1%

Risk Phrases

R22 – Harmful if swallowed

R36/38 – Eye & Skin irritant: Avoid prolonged exposure

R37 – Respiratory System irritant: May cause nausea. Avoid inhalation

HAZARDS IDENTIFICATION

Non Hazardous product in normal conditions of use. Inflammable and acidic.

Stable under normal conditions.

FIRST AID MEASURES

Ingestion: Immediately evacuate any remaining liquid from the mouth and seek immediate medical attention.

DO NOT drink water and DO NOT induce vomiting.

Eye contact: Immediately irrigate eye with clean water for 15 minutes and seek medical advice if irritation persists.

Skin Contact: Wash off with soap and plenty of water. Avoid prolonged exposure.

Inhalation: Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration and seek immediate medical attention.

FIRE FIGHTING MEASURES

Extinguished Media:

Carbon dioxide foam, dry chemical or fine spray water extinguisher

Unusual fire and explosion hazards:

None known

Fire fighting equipment:

Breathing apparatus

Other recommendations:

Cool exposed containers with water

ACCIDENTAL RELEASE MEASURES

Spillage Actions:

Ventilate the area and avoid inhaling vapours. Contain & absorb spillage with sand, sawdust or earth. Place in closed containers and dispose of in accordance with local waste regulations. Do not pour product in drains, sewers or rivers.

HANDLING AND STORAGE

Handling in use:

Avoid contact with eyes and prolonged contact with skin. Areas of storage, preparation and application should be well ventilated. Smoking, eating and drinking should be prohibited in all preparation and application areas.

Handling in Storage:

Handle containers carefully to prevent damage and spillage. Keep product in its original container. Keep container closed when not in use. Naked flames and smoking should not be permitted in storage areas.

Storage:

Store in a well ventilated, dry place away from sources of flame, heat and direct sunlight.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Exposure	Limits		
	ppm	mg	time
Inhalation	64,000		04 hours
Skin	200	595	24 hours
Eyes	40	119	24 hours

Special Protection:

Workers should use appropriate certified respiratory masks with dust filters. Wear safety eyewear, complying with BS 2092. Disposal latex gloves and industrial overalls are recommended.

PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Colour:	Colourless
Odour:	Solvent
Specific Gravity:	0.95
Flash Point:	3C°
VOCs:	<1%
Solubility in water:	slight

STABILITY AND REACTIVITY

Stability:

Stable under recommended storage, handling and usage conditions

Hazardous decomposition products:

Combustion can produce carbon monoxide (CO)

Materials to avoid:

Strong oxidising agents

TOXICOLOGICAL INFORMATION

Health Hazards:

May be irritating for skin and eyes after prolonged contact. Repeated or long exposure may cause removal of natural fat from the skin resulting in dryness and possible dermatitis.

ECOLOGICAL INFORMATION

This product is not classified as dangerous for the environment.
Product should not be allowed to enter drains or water courses.

DISPOSAL CONSIDERATIONS

Can be disposed of in accordance with local waste regulations.
Do not allow into drains or water courses.

TRANSPORT INFORMATION

E.U. Regulations: Non hazardous for transport

Shipping name/DOT class: Paint/3

UN No: 1263

Packaging: III

REGULATORY INFORMATION

Limited exposure value on work sight:

None known

Risk Phrases:

R22 – Harmful if swallowed

R36/38 – Eye & Skin irritant: Avoid prolonged exposure

R37 – Respiratory system irritant: May cause nausea & avoid inhalation

Safety Phrases:

S36/37 – Wear suitable protective clothing and gloves

S61 – Avoid release to the environment. Refer to special instructions/safety data sheet.

S62 – If swallowed, DO NOT induce vomiting: Seek medical advice immediately and show this container or label.

OTHER INFORMATION

Recommended uses and restrictions

The information in this MSDS is based on the present state of our knowledge and on current EEC and national laws.
This product should not be used for purposes other than shown in the product data sheet.