



11848 152 Street NW  
Edmonton, AB, T5V 1E3  
Phone: (780) 443-4100 Fax: (780) 489-5589  
Toll Free: 1-888-443-4182

## Acrylic Cleaning Advice

### Dusting

Always damp dust acrylic sheet, for best results, mix a solution of one teaspoon of dishwashing liquid, or other mild soap or detergent, and a pint of water; apply this solution to acrylic sheet with an atomizer or spray bottle and wipe until dry and glossy smooth with a clean cotton flannel or jersey cloth.

Do not use dishwashing liquid containing hand lotions, such as aloe or lanolin.

### Cleaning

To clean acrylic sheet, wash with plenty of mild soap or detergent and lukewarm water using the bare hand to feel and dislodge any caked dirt or mud. A soft cloth, sponge or chamois may be used, but only as a means of carrying water to the plastic. Rinse well. Dry by blotting with a clean damp cloth or chamois. Rubbing a dirty surface with a dry cloth will scratch the material. In addition, rubbing builds up an electrostatic charge on the acrylic sheet so that it attracts dust particles from the air. Wiping with a damp chamois will remove this charge as well as the dust. Do not use window cleaning fluids, scouring compounds, leaded or ethyl gasoline, benzene, acetone, carbon tetrachloride, fire extinguisher or de-icing fluid, lacquer thinners, or other strong solvents. To remove tar, grease, paint, etc., use a good grade of VM&P naphtha, kerosene, or other aliphatic hydrocarbon compound.

### Polishing

If, after washing, the acrylic sheet surface shows minor scratches, most can be removed or reduced by application of polish. To apply polishes, use a small pad of soft cotton flannel dampened with water. Rub the sheet along the length of the scratches with a back and forth motion (or use a circular motion). Avoid excess rubbing on any one spot. Several applications may be necessary, but most minor scratches can be reduced and the clarity improved within a relatively short time. After waxing, wipe with a clean damp cloth to remove static charges that may attract dust particles. Do not use wipe with a clean damp cloth to remove static charges that may attract dust particles. Do not use household spray waxes, as many of these contain agents harmful to the surface of acrylic sheet.

***\*Nonwarranty:** The information contained in this program is presented in good faith and is believed to be accurate, but without guarantee. Conditions of use are beyond our control and all risks are assumed by the user. Nothing herein is a recommendation for uses which infringe valid patents or as extending a license under valid patents.*