

Undercabinet 30" Ventilation Hood

Ventilation

Available Products: FCVW3062AD, FCVW3062AS

Available Colors: Black Stainless Steel, Stainless Steel

Version: 12/23



Product Specifications

Ventilation System

Ventilation Options	Convertible
Ducted Vent	Optional (See Manual)
Ductless Vent	Yes - Out of the Box
Exhaust Fan Speeds	3
Maximum Air Flow Capacity	330 CFM
Minimum Air Flow Capacity	110 CFM
Maximum Sones Rating	10.1 sone
Minimum Sones Rating	1.7 sone
Grease Filter Included	Yes
Grease Filter Quantity	2
Grease Filter Type	Aluminum Mesh
Grease Filter Dishwasher Safe	Yes
Charcoal Filter Included	Yes
Charcoal Filter Quantity	2

Surface Light System

Lighting Type	LED Strip
Number of Lights	1
Number of Light Settings	3

Electrical Specifications

Voltage Rating	120 V
Watts @ 120 Volts	114 Watts

General Specifications

Prop 65 Label	Yes
Warranty - Labor	1 Year
Warranty - Parts	1 Year

Safety Certifications and Approvals

UL Listed	Yes
cUL Listed	Yes

Controls

Control Type	Glass Touch
Filter Change Indicator	Yes

Dimensions and Volume

Height	4 15/16"
Width	30"
Depth	19 3/4"


Installation

Duct Exit Location	Top
Hardwired	Yes
Power Supply Connection Type	Hard Wired

Certifications and Approvals

HVI Listed	Yes
------------	-----

Installation Diagram



	Dim A	Dim B
FCVW3062AS	30" (76.2 cm)	6 9/16" (16.7 cm)
FCVW3062AD		
FCVW3062AS	36" (91.4 cm)	9 1/2" (24.3 cm)