# **Product Datasheet**



## **REX Slim**


REX Slim 150W Commercial Floodlight 240V + Photocell N6066


#### **Features & Applications**



- Slim line size for more discrete install
- Less weight means easier install and smaller fixings
- Energy saving highly efficient LED's
- No driver required
- Efficient replacement for Metal Halide or SON fittings
- Photocell allows for auto on/off between day and night
- Ideal for industrial and commercial applications like building fronts, construction sites and garages

### **Dimensions & Weight**





Length	Width	Height	Weight
333mm	51mm	420mm	





### **Technical Specification**

Electrical Specifications	
Operating Wattage	150W
Operating Voltage	AC 220V-240V
Operating Frequency	50-60Hz
Power Factor	≥0.9

Photometric Specifications		
Colour Temperature	4000K	
Light Colour	Cool White	
Luminous Flux	13500 lm	
Luminous Efficiency	90 lm/W	
Colour Rendering Index	≥70	
Beam Angle	120°	

Photocell Specs		
On-Off Levels	10~20Lx On (Dusk); 30~60Lx Off(Dawn)	
Ambient Temp	-40°C ~ +70°C	
Power Consumption	1.5VA Max	
Electrical Life	6500 Cycles	

Material Specifications	
Construction Materials	Aluminium Body & Toughened Glass
Product Colour	Black
Cable Length	1.5m

Additional Product Specifications	
Replaceable Lamp	No
Dimmable	No
Lifespan	30,000hrs

Standards, Certificates & Warranty		
IP Protection Rating	IP65	
IK Protection Rating	IK08	
Standards	CE / LVD / RoSH	
Warranty Period	3 Years	