

WIRING & DRIVERS

TECHNICAL SPECIFICATION SHEET



PLD UNI-DRIVE 350MA

1-10V DIMMABLE LED DRIVER (SERIES)

Features & Benefits

Constant current LED driver

1-10V & press to make compatible

For 1-10 1W LED

Min/Max load: 1-10 x LEDs @ 350mA

Sync up to 10 units for dimming
(1m sync cable included)

PRODUCT DATA

Product Code	PLD UNI-DRIVE 350MA
--------------	---------------------

ELECTRICAL CHARACTERISTICS

	INPUT		OUTPUT		Power factor
	Current	Voltage	Current	Voltage	
Rated wattage					
15W	N/A	220-240V	350mA	49V MAX	0.98

GENERAL

Ambient temp (ta = °C)	-25 to +50
Case temp (tc = °C)	75
Control	Dimmable 1-10V & press to make. Sync up to 10 units with supplied cable.
Double insulation	Yes
Efficiency (%)	80
Inrush current	5A 0.05ms
IP rating	20
Loop in / Loop out	No
Protection	Mains surge, short circuit, over-load & over heating (over heating can be reset)
SELV (separated extra low voltage)	Yes
Weight (g)	100

WIRING

Connection output	Terminals
Input cable	0.5-1.5mm² MAX
Output cable	0.5-1.5mm² MAX

ACCESSORIES

Product code	Description
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types
SYNC CABLE 4M	4m sync cable

GUARANTEE

5 years

Dimensions

