



**COLLINGWOOD
LIGHTING**



FEATURES & BENEFITS

- › Equivalent to 20W halogen
- › Complete with wall fixings
- › Adjustable angle to direct light
- › Copper for antique effect (WL320A)
- › Suitable for indoor and outdoor use

WL220A | WL020A BLK | WL320A

LED wall light



Suitable for use outdoors



3-year extended warranty available



Also available in RGB (WL220A / WL020A)



Patent information: collingwoodlighting.com/patent

WL220A / WL020A

WL320A

ZONE

L70, B10

3SDCM

PHOTOMETRICS @ 25°C

Colour	Beam angle	Product code	CRI	lm	lm/W	lx at 1m
4000K	38°	WL220A F NW	>70Ra	310	103	705
	18°	WL220A S NW	>70Ra	310	103	2823
	38°	WL020A BLK F NW	>70Ra	310	103	705
	18°	WL020A BLK S NW	>70Ra	310	103	2823
3000K	38°	WL320A F NW	>70Ra	310	103	705
	18°	WL220A F WW	>80Ra	265	88	602
	18°	WL220A S WW	>80Ra	265	88	2413
	38°	WL020A BLK F WW	>80Ra	265	88	602
	18°	WL020A BLK S WW	>80Ra	265	88	2413
	38°	WL320A F WW	>80Ra	265	88	602

GENERAL

Construction material: WL220A / WL020A: Anodised aluminium WL320A: Copper

WIRING

Cable / flying lead: 0.05 [0.205mm² red & black PTFE]

Type of wiring required: Series


LED DRIVERS

Bathroom zone applicable to fitting only

Product code	mA	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	350	Yes	No	1	1	3
PLR/350 1-5	350	Yes	No	1	1	1
PLD UNI-DRIVE 350MA	350	Yes	Yes (1-10V)	2	1	3

ACCESSORIES

Product code	Description
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types



4000K 18° / 4000K 38°

Additional diagrams available at collingwoodlighting.com

