

### MODEL 1110

Features optical sensors that are designed to match the response of the human eye




### SPECIFICATIONS

MODELS	1110	
Measurement Range	.01 lx to 200,000lx	0.01 fc to 18,580 fc
Accuracy	±3% of R on incandescent sources ±6% of R on LEDs (3,000K to 6,000K) ±9% of R on fluorescent sources	
Accuracy with compensation	LED mode: ±4% of R (at 4,000K) Flou mode: ±4% of R (type F11, 4,000K)	
Display Resolution	0.1 lx (0.1 lx to 999.9 lx) 1 lx (1,000 lx to 9,999 lx) 10 lx (10,000 lx to 99.99 klx) 100 lx beyond	0.01 fc (0.01 fc to 99.99 fc) 0.1 fc (100.0 fc to 999.9 fc) 1 fc (1,000 fc to 9,999 fc) 10 fc beyond
Recording	Manual start/stop on the product Short press for MEM: spot recording/long press for REC at the defined default rate Programed recording: start date, recording interval, and end date defined using DataView® software	
Other Functions	MIN-AVG-MAX-HOLD	
Sampling Rate	Programmable from 1s, 2s, 5s, 10s, 20s, 30s, 2min, 5min, 10min, 15min, 30min, and 1hr	
MAP mode	The MAP mode can be used to map the lighting on the surface of a room. In this case the measurements are saved in the same file	
Memory	1,000,000 measurements on each channel (4MB). Recorded data is stored in non-volatile memory and will be retained even if battery is low or removed.	
Communication	USB 2.0 and Bluetooth	
Power Source	3x1.5V AA (LR6) alkaline batteries or USB port (micro-USB adaptor offered as an accessory)	
Battery Life	500hrs, 3yrs with 15min intervals	
Dimensions	Case: 5.9 x 2.84 x 1.28" (150 x 72 x 32mm) Sensor: 2.64 x 2.52 x 1.38" (67 x 64 x 35mm)	
Weight (with battery)	12.2 oz (345g) with batteries	
Case	Polycarbonate	
Operating temperature	14° to 140°F (-10° to 60°C)	
Storage temperature	-4° to 140°F (-20° to 60°C)	
Relative Humidity	Up to 90%	
Ingress Protection (IP)	IP50 with USB connector closed and protective cap on sensor	
EMC	EN 61326-1	
Safety Compliance	IEC 61010-1	
Warranty	2 years	



### FEATURES

- User selectable light source, natural, LED or fluorescent
- Spectral error compensation for LED and fluorescent lighting
- Removable light sensor with expandable cable up to 48"
- Map mode profiles the illuminance map of the area or room by storing multiple measurements
- Min, Max, and Average measurements stored
- Free app for Android™ from the Google® Play Store
- Spot or continuous recording of up to 1,000,000 measurements stored in 8MB flash memory
- Blue luminescent backlit display
- User selectable Foot Candle or Lux units
- USB and Bluetooth communication
- Magnetic mount
- Battery or USB powered
- DataView® graphing and analysis software included



Measure and record multiple measurements to create an illuminance map of the room or area of interest

#### CATALOG NO.

#### DESCRIPTION

2121.71 Lightmeter Data Logger Model 1110

Accessories/Replacement - available on website store from [www.aemc.com](http://www.aemc.com)

2118.65 Soft Carrying Case

2138.66 Cable - 6 ft USB Type A - Type B Micro

2118.09 General Purpose Carrying Case

2122.31 Shock Proof Housing

2153.78 Adapter - US Wall Plug to USB

5000.44 Multifix Universal Mounting System