


# BougeRV

BJ100W-B-B016

Bifacial 100W Monocrystalline Solar Panel




Front Profile (unit cm)



MC4 Negative



MC4 Positive



Back Profile (unit cm)

Side Profile (unit cm)

## Electrical Data (STC)

Maximum Power (Pmax)	100W±5%
Solar Cells Efficiency	23%
Max. Power Voltage (Vmp)	17.1V±5%
Max. Power Current (Imp)	5.8A±5%
Open Circuit Voltage (Voc)	20.1V±5%
Short Circuit Current (Isc)	6.1A±5%
Max. System Voltage	1000V DC
Max. Series Fuse Rating	15A
"STC: Irradiance: 1000W/m <sup>2</sup> , Temperature: 25°C, Air Mass: 1.5"	

## Mechanical Data

Mono Solar Cells	10BB 7.2 x 3.6 in (182 x 91mm)
Number of Cells	30 (3 x 10)
Dimension	39.0 x 23.1 x 1.4 in (990 x 586 x 35 mm)
Weight	14.1lb (6.4KG)
Front Tempered Glass	0.13in (3.2mm)
Junction Box	IP68
MC4 Cables	14 AWG(2.5mm <sup>2</sup> ) 3FT (900mm)
Frame	Anodized Aluminum Alloy

## Temperature Characteristics

Temperature Coefficient of Pmax	-0.39%/°C
Temperature Coefficient of Voc	-0.33%/°C
Temperature Coefficient of Isc	-0.06%/°C
Operating Temperature Limits	-40°F~+185°F / -40°C~+85°C

## Warranty

10 years Material & workmanship warranty

25 years Linear power output warranty

(Please refer to product warranty for details)

## ⚠ WARNING ELECTRICAL HAZARD

Before using this product, please read the user manual carefully and properly keep for reference.

## CONTACT US

✉ (Amazon US/CA) service@bougeerv.com  
(BougeRV Website) support@bougeerv.com

☎ 1-408-656-8402 (Mon.-Fri. 9 am - 6 pm PST)

🌐 www.bougeerv.com  1-669-232-7427

Made in Malaysia

