



BI-LEVEL VERSACOOLER® II

Energy and Water Conservation Technology PG8ACSL, PGACSL

Suggested Specification

Model PG8ACSL shall deliver 8.0 gph of 50° F degree water at 90° F ambient and 80° F inlet water. Model PGACSL is a non-refrigerated drinking fountain and delivers ambient water. Shall include four antimicrobial copper push pads. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Cabinet finish shall be sandstone on galvanized steel or brushed stainless steel. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with ANSI/NSF 61 and NSF/ANSI 372.

Models

- PG8ACSL delivers 8.0 gallons of chilled drinking water per hour
- PGACSL is a non-refrigerated fountain

Standard Features

- Universal design allows universal installation
- Built-in 100 micron strainer stops particles before they enter the waterway
- Waterways are Lead-Free in materials & construction
- Flexible and one-piece water saver bubbler
- Stainless steel top and heavy duty galvanized steel frame
- Four antimicrobial copper push pads per side
- External stream height adjustment
- Mechanical activation

Finishes

- Standard cabinet finish: Sandstone powder coated paint on galvanized steel
- Optional finishes (at additional cost): Stainless steel

Installation

- Prior to roughing consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation

Options (at additional cost)

- Push handle glass fillers (029603-004)
- One piece chrome plated brass bubbler (036700-001)
- Cane apron (035174-001)
- VersaFilter

Limited 5-Year Warranty

(Continental limits of the United States and Canada)
Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Antimicrobial Copper - EPA Registration No. 89187-3
- Oasis International Electric Water Coolers are listed by Underwriters Laboratories Inc. and comply with both U.S. and Canadian Requirements.
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.
- This unit complies with ARI standard 1010 Testing, Operating and Rating requirements (electric water coolers only).
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed.



| Model | 50° F Drinking Water 90° F Ambient Air Temp* | | | Hot'N Cold Model | 115 Volts, 60 HZ | | | Glass Filler Acc. Option | Cabinet Color Finish | Net Wt. Approx |
|---------|---|------------------|------------|---------------------|------------------|-------------------|-------------|-----------------------------|-------------------------|-------------------|
| | Rated Capacity GHP | Base Rate GHP | Pre-Cooler | | Compr. HP | Full Load Amps | Rated Watts | | | |
| PG8ACSL | 8.0 | 8.0 | No | No | 1/4 | 4.4 | 460 | Yes | Yes | 94 Lbs |
| PGACSL | Fountain Only | | | | | | | Yes | Yes | 64 Lbs |

* Industry standard rating condition 80° F inlet water temperature

Specifications subject to change without notice

