

We Know Water.

VERSACOOLER® II WITH CONTACTLESS VERSAFILLER®

PG8EBF PGEBF

Suggested Specification

Model PG8EBF shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. PGEBF is a nonrefrigerated model and delivers ambient drinking water. Shall include the VersaFiller® with contactless activation and laminar flow; lower unit shall have four push pads to activate the manual flow of water for the cooler. Bottle Filler alcove and cabinet finish shall be stainless steel. Key VersaFiller components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible quard and operate between 20 and 100 PSI. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ ANSI 61 and NSF/ANSI 372.

		PG8EBF	PGEBF	
Features:	•	Built-in 100 micron strainer stops particles before they enter the waterway		
		Waterways are Lead-Free in materials & construction		
		High efficiency cooling system		
		Stainless steel top and heavy duty galvanized steel frame		
		Contactless activation bottle filler with programmable auto shut off		
		Ample space within the bottle filler cabinet to add filtration, including all OASIS filters		
		Flexible one-piece water saver bubbler infused with silver-based antimicrobial additive		
		Includes integral self-scouring waste drain		
		External access to stream height adjustment on lower VersaCooler fountain		
	•	External access to thermostat with tool activated OFF position		
		Built-in filter monitor and bottle counter		
	•	Logos permanently formed into the alcove and stainless steel wrapper		
	- LED lighted alcove			
Filtration:	Option to add filtration			
Power:	115 Volts, 60 Hz			
Activation By:	Contactless Sensor on Bottle Filler and Manual Activation on Fountain			
Mounting Type:	Wall Mounted			
Chilling Option:	8.0 gph		Non-Refrigerated	
Full Load Amps:	5.0 amps		0.2 amps	
Rated Watts:	500		11	
Approx. Net Weight:	62 lbs		31 lbs	
Installation Location:	Indoor			



Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- · Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation

Finishes

- Standard cabinet finish: Greystone powder coated paint on galvanized steel
- Optional finishes: Sandstone powder coated paint; Stainless steel (at additional cost)

Options

- · One piece chrome plated brass bubbler (036700-001)
- · Cane apron (035174-002)
- · OASIS Versafilter III Kit 041253-001

Limited 5-Year Warranty

(Continental limits of the United States and Canada)
Five years on the sealed refrigeration system and most
component parts. Detailed warranty certificate enclosed
with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These waters coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed











Cancer and Reproductive Harm www.P65Warnings.ca.gov

*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

OASIS VERSACOOLER® II WITH CONTACTLESS VERSAFILLER®

