

# We Know Water.

# **VERSACOOLER® II WITH VERSAFILTER**

## PG8SBF • PGSBF

## **Suggested Specification**

Features:

JIPART

TOLL FREE: 800-442-6622

PITTSBURGH: 412-781-9100

www.equiparts.com

Location:

That Hard to Find Part is Right Here!

Repair Parts Specialists

Model PG8SBF shall deliver 8.0 gph of 50°F water at 90°F ambient and 80° Finlet water per ASHRAE 18 testing. Model PGSBF is a nonrefrigerated fountain and delivers ambient water. Model PG8SBF shall include PG8AC and the VersaFiller Sports Bottle Filler independent push button manual activation; lower unit shall have four push pads to activate the manual flow of water for the cooler. Bottle Filler alcove and cabinet finish shall be stainless steel. Key VersaFiller components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Cabinet finish shall be brushed stainless steel. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.

PG8SBF PGSBF	:
--------------	---

- Built-in 100 micron strainer stops particles before they enter the waterway
- Waterways are Lead-Free in materials & construction
- High efficiency cooling system
- Stainless steel top and heavy duty galvanized steel frame
- Ample space within the bottle filler cabinet to add filtration, including all OASIS filters
- Access through the top of the bottle filler for clean and easy replacement of filters with Tilt
- Flexible one-piece water saver bubbler infused with silver-based antimicrobial additive

Includes integral self-scouring waste drain

External access to stream height adjustment on lower VersaCooler fountain

External access to thermostat with tool activated OFF position

Logos permanently formed into the alcove and stainless steel wrapper

Filtration:	Option to add filtration to top of bottle filler		
Power:	115 Volts, 60 Hz		
Activation By:	Independent Manual Activation on Bottle Filler and Fountain		
Mounting Type:	Wall Mounted		

	Fountain  Wall Mounted	
Mounting Type:		
Chilling Option:	8.0 gph*	Non-Refrigerated
Full Load Amps:	5.0 amps	0 amps
Rated Watts:	500	0
Approx. Net Weight:	61 lbs	30 lbs
Installation	la de co	

 $<sup>^{\</sup>circ}$  Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

Indoor



#### Installation

- Prior to roughing in, consult with local, state and federal codes for proper mounting height
- · Shipped with complete instructions and wall mounting bracket

#### **Finishes**

- Standard cabinet finish: Greystone powder coated paint on galvanized steel
- Optional finishes: Sandstone powder coated paint; Stainless steel (at additional cost)

#### **Options**

- · One piece chrome plated brass bubbler (036700-001)
- · Cane apron (035174-002)
- OASIS Versafilter III Kit 041253-001

### **Limited 5-Year Warranty**

(Continental limits of the United States and Canada)
Five years on the sealed refrigeration system and most component
parts. Detailed warranty certificate enclosed with each bottle filler;
sample available upon request.

#### **Export Warranty**

One year on component parts. Detailed warranty certificate enclosed with each bottle filler; sample copy available upon request.

## **Compliance**

- Certified to UL 399 and CAN/CSA C22.2 No. 120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- Complies with the requirements of ADA (Americans with Disabilities Act) when properly installed



# WARNING:

Cancer and Reproductive Harm www.P65Warnings.ca.gov











# **OASIS® VERSACOOLER II WITH VERSAFILLER**



