

We Know Water.


VANDAL-RESISTANT. VERSACOOLER® II WITH CONTACTLESS VERSAFILLER®

PGV8EBF PGVEBF

Suggested Specification

Model PGV8EBF shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. PGVEBF is a nonrefrigerated model and delivers ambient drinking water. Shall include the VersaFiller® with contactless activation and laminar flow; lower unit shall have a single vandal resistant push button to activate the manual flow of water for the cooler. Bottle Filler alcove and cabinet finish shall be stainless steel. Key VersaFiller components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Cabinet finish shall be brushed stainless steel. Cabinet shall have galvanized steel screens to prevent objects from being inserted into ventilation panels or underside of unit. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ ANSI 61 and NSF/ANSI 372.

		PGV8EBF	PGVEBF	
		Built-in 100 micron strainer stops particles before they enter the waterway		
	•	Waterways are Lead-Free in materials & construction		
Features:	•	Vandal resistant water saver bubbler infused with silver-based antimicrobial additive		
		Vandal resistant fasteners		
		Galvanized steel louver and bottom screens		
		High efficiency cooling system		
	٠	Stainless steel top and heavy duty galvanized steel frame		
	•	Contactless activation bottle filler with programmable auto shut off		
		Ample space within the bottle filler cabinet to add filtration, including all OASIS filters		
		Includes integral self-scouring waste drain		
	•	External access to stream height adjustment on lower VersaCooler fountain		
	٠	External access to thermostat with tool activated OFF position		
		Built-in filter monitor and bottle counter		
	٠	Logos permanently formed into the alcove and stainless steel wrapper		
		LED lighted alcove		
Filtration:		Option to add filtration		
Power:		115 Volts, 60 Hz		



Contactless Sensor on Bottle Filler and





Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation

Finishes

Standard cabinet finish: Stainless steel

Options

- One piece chrome plated brass bubbler (036700-001)
- Cane apron (035174-003)
- OASIS Versafilter III Kit 041253-001

Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These waters coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



WARNING:

Cancer and Reproductive Harm www.P65Warnings.ca.gov











OASIS VANDAL-RESISTANT, VERSACOOLER® II WITH CONTACTLESS VERSAFILLER®

