



**We Know Water.**

**VERSACOOLER® II WITH CONTACTLESS VERSAFILLER®  
WITH VERSAFILTER™ III**

- **PG8FEBF**
- **PGFEBF**

**Suggested Specification**

Model PG8FEBF shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model PGFEBF is a non-refrigerated model and delivers ambient drinking water. Shall include the VersaFiller® with contactless activation and laminar flow; lower unit shall have four push pads to activate the manual flow of water for the cooler. Bottle Filler alcove and cabinet finish shall be stainless steel. Key VersaFiller components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards, and comply with NSF/ANSI 61 and NSF/ANSI 372.



	PG8FEBF	PGFEBF
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Built-in 100 micron strainer stops particles before they enter the waterway</li> <li>• Waterways are lead-free in materials &amp; construction</li> <li>• High efficiency cooling system</li> <li>• Stainless steel top and heavy duty galvanized steel frame</li> <li>• Contactless activation bottle filler with programmable auto shut off</li> <li>• Ample space within the bottle filler cabinet to add filtration, including all OASIS filters</li> <li>• Flexible one-piece water saver bubbler infused with silver-based antimicrobial additive</li> <li>• Includes integral self-scouring waste drain</li> <li>• External access to stream height adjustment on lower Versacooler fountain</li> <li>• External access to thermostat with tool activated OFF position</li> <li>• VersaFilter III located in top bottle filler for easy filter replacement with Tilt 'N Tether</li> <li>• Built-in filter monitor and bottle counter</li> <li>• Logos permanently formed into the alcove and stainless steel wrapper</li> <li>• LED lighted alcove</li> </ul>	
<b>Filtration:</b>	VersaFilter III is Certified to NSF/ANSI 42 and 53 for lead, cyst, Particulate Class I, chlorine, taste and odor reduction to 4,750 gallons	
<b>Power:</b>	115 Volts, 60 Hz	
<b>Activation By:</b>	Contactless Sensor on Bottle Filler and Manual Activation on Fountain	
<b>Mounting Type:</b>	Wall Mounted	
<b>Chilling Option:</b>	8.0 gph*	Non-refrigerated
<b>Full Load Amps:</b>	5.0 amps	0.2 amps
<b>Rated Watts:</b>	500	11
<b>Approx. Net Weight:</b>	64	33
<b>Installation Location:</b>	Indoor	

**Installation**

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation.

**Finishes**

- Standard: Greystone powder coat on galvanized steel
- Sandstone powder coat on galvanized steel; stainless steel (at additional cost)

**Options**

- One piece chrome plated brass bubbler (036700-001)
- Cane apron (035174-002)

**Limited 5-Year Warranty**

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

**Export Warranty**

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

**Certifications/Compliance**

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These waters coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed




**WARNING:**  
Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

Specifications subject to change without notice

# VERSACOOLER® II WITH CONTACTLESS VERSAFILLER® WITH VERSAFILTER™ III



**EQUIPARTS**  
Repair Parts Specialists

TOLL FREE: 800-442-6622  
PITTSBURGH: 412-781-9100  
[www.equiparts.com](http://www.equiparts.com)

*That Hard to Find Part is Right Here!*