PANEL

| Screen Size | 75" Class (74.52" diag) |
|--|--|
| Panel Technology | IPS |
| Aspect Ratio | 16:9 |
| Native Resolution | 3,840 x 2,160 (UHD), M+ |
| Brightness(Typ., with Protective Glass, cd/m²) | 3000 |
| Contrast Ratio | 1,200:1 |
| Viewing Angle (HxV) | 178 x 178 |
| Response Time | 8 ms (Typ.) (G to G BW) |
| Surface Treatment | Hard coating (2H),Anti-glare treatment of the front polarizer (Haze 3% (Typ.)) |
| QWP Polarizer (FPR Film) | Yes |
| Local dimming | 48 Block |
| Orientation | Portrait only |
| CONNECTIVITY | |
| Input | HDMI, DP, DVI-D, Audio |
| Output | DP, External Speaker (*waterproof speakers are mandatory for outdoor installation) |
| External Control | RS232C, RJ45, SD Card, USB 3.0 |

| 4/14/23, 3:33 PM | about:blank |
|--|---|
| Front glass | 9.5 mm (AR, Front Safety Vandal Glass) |
| Bezel Color | Medium Texture Black (Common color) |
| Bezel Width | 110 mm (T), 230 mm (B), 73.3.0 mm (L/R) |
| Monitor Dimension (W x H x D) | 1,075.6 x 1,991.6 x 218.9 mm |
| Weight (Head) | 180 kg |
| Monitor with Optional Stand Dimensions (W x H x D) | 1,075.6 x 2,361.6 x 218.9 mm |
| Packing Dimensions (W x H x D) | 1,308 x 2,296 x 468 mm |
| Packed Weight | 15 kg (TBD) |
| Handle | Option (I-Bolt) |
| SPECIAL FEATURES | |
| Yes | Temperature Sensor, Tile Mode, Natural Mode@Tile Mode, Auto- Brightness Sensor, Pixel Sensor, Cooling Fan, ISM Method, DPM Select, Energy Saving, Smart Energy Saving, File Play with USB, Internal Memory (8 GB), Easy Brightness Control, Content Scheduling, Fail over, DP daisy chain |
| ENVIRONMENT CONDITIONS | |
| Operation Tempature | -30 °C to 50 °C |
| Operation Humidity | 5% ~ 100% |
| Direct Sunlight | Yes |
| Dust / Water Proofing | IP 56 |

POWER

about:blank

| Power Supply | 100-240V~, 50/60Hz |
|---------------------------------------|--------------------|
| Power Type | Built-In Power |
| Power Consumption Typ. / Max. | 700 W / 1,000 W |
| Power Consumption Smart Energy Saving | 350 W |

| STANDARD(CERTIFICATION) |
|-------------------------|
|-------------------------|

| Safety | UL/cUL/CB |
|-------------------|--------------------------|
| EMC | FCC Class "A" / CE / KCC |
| ErP / Energy Star | No / No |

MEDIA PLAYER COMPATIBILITY

| OPS type compatible | No |
|----------------------------------|----|
| External Media Player Attachable | No |

SOFTWARE COMPATIILITY

| SuperSign W/Lite | Yes |
|----------------------|--|
| SuperSign C | Yes |
| ACCESSORIES | |
| Accessories | Remote controller, EIG, ESG, Regulation book, Phone to RS232C gender, USB cable, HDMI cable |
| Optional Accessories | Media player (driven by customer), Enclosure Stand (ST-750X) |