Slim & Robust Design with Outstanding Visibility

Ultra High Brightness Outdoor Display (55) XE4F Series



With a tough design that is also remarkably slim and lightweight, the XE4F Series can be easily installed to meet needs in a variety of custom outdoor environments. With upgraded brightness, the XE4F displays can capture customers' attention even under direct sunlight.



Slim & Light



Outstanding Visibility



IP56 Rated Dust/Water Proof



Easy Data Control & Maintenance








Slim & Light Design

XE4F series composed of single display with a light and slim design and it can be easily customized to suit various external environments with no need for separate casing.

Easy integration for partner's customized design

Because the XE4F Series is significantly thinner and lighter than previous designs, it is mount-ready and can be more easily customized for a variety of applications.





Bright & Brilliant

The XE4F series possess powerful brightness of 4,000nits, providing clear and vivid picture quality even under direct sunlight.

National Museum

Wide Viewing Angle

IPS technology provides better control of the liquid crystals, which in turn allows the screen to be viewed at virtually any angle.



Long Lasting Brightness

With a powerful brightness of 4,000 nits and wide viewing angles, the XE4F Series delivers content clearly and catches the attention of viewers no matter where they are, making it the ultimate display for outdoor visibility.

Visible with Polarized Sunglasses

Quarter Wave Plate technology in this display enables clear visibility even when the viewer is wearing polarized sunglasses.





Secured Protection with IP56 Design

The XE4F Series is rated IP56 for protection against dust and liquids so that it can serve reliably outdoors in almost all kinds of weather.

Direct Sunlight Dust Protection Protection STATION 07-010 Protection Protection

Protective Glass (IK10 Certified)

The tempered and laminated front glass ensures optimum protection from outdoor extremities, reducing / minimizing damage from external impacts.



- * The image is for illustrative purposes only
- **IK rating refers to the degree of resistance against external impacts on a scale of 0 to 10. (10 indicates the highest level of protection.)


Support for HDBaseT™

The XE4F Series supports the HDBaseT global standartd fo the transmission of ultra-high definition video and audio, Ethernet, controls, USB and IR over a single, long-distance cable for easier control of the display.




Web Monitoring


The embedded web monitoring allows a variety of parameters to be diagnosed in real time using temperature, pixel, door, ambient light and gyro sensors. It can be easily controlled at all times.



55XE4F



49XE4F



CONNECTIVITY



- SPEAKER OUT
- 2 HDMIIN
- **3** RS232C IN
- 4 RS232C OUT
- 5 DP IN
- **6** USB IN 9 HDBaseT IN

7 LAN IN

8 LAN OUT



IP-Rated Outdoor Display | XE4F Series

$\overline{}$	$\overline{}$
55][

-			FEVE 45	401/545				EEVE 4E	40\/E4E
	Model		55XE4F	49XE4F		Model		55XE4F	49XE4F
	Screen Size Panel Technology		55"	49"		webOS ver.		webOS 4.0	webOS 4.0
			IPS	IPS			USB Auto		
	Back Light	Type	Direct	Direct			Playback	Yes	Yes
	Aspect Ra		16:9	16:9	_	Embedded	Local Contents		
	Native Re	colution	1,920 x 1,080 (FHD, WRGB)	1,920 x 1,080 (FHD, WRGB)		CMS	Color Contents	Yes	Yes
	Refresh R	nto.	60Hz	60Hz			Scheduling		
			T - 4.000 - 1. MAI - 2.200 - 1.				Group Manager	Yes	Yes
	Brightness Contrast Ratio Dynamic CR Color gamut		Typ. 4,000nit, Min. 3,200nit	Typ. 4,000nit, Min. 3,200nit		Fail over		Yes	Yes
PANEL			1,200:1 500,000:1	1,300:1 500,000:1		Image	Booting Logo	Yes	Yes
			500,000:1	500,000:1		Customization	No Signal	Yes	Yes
			72%	72%		Customization	DC 232C	Yes	Yes
	Viewing Angle(H x V)		178 x 178	178 x 178		6	RS-232C		
	Color Dep	h	1.07 Billon (10bit) 8 ms	1.07 Billon (10bit) 8 ms		Content Sync.	Backlight sync	Yes	Yes
	Docnopco	Time (G to G)					Local Network	Yes	Yes
	Cocons						PIP	Yes	Yes
	Surface Treatment(Haze) OWP(Quarter Wave Plate) Life time(Typ.) Operation Hours Orientation		Haze 3%	Haze 3%		Multi-screen Screen Share	PIP PBP	Yes (2)	Yes (2)
			Yes	Yes s 50,000 Hrs				No	No
			50,000 Hrs			Video Tag		Yes (4)	Yes (4)
			24 Hrs	24 Hrs		Diameter LIDI			
			Portrait & Landscape	Portrait & Landscape		Play via ÜRL		Yes	Yes
			Voc (2) UDCD2 2	Voc (2) LIDCD2 2		OSD Rotation		Yes	Yes
		HDMI	Yes (2), HDCP2.2 Yes (1), HDCP1.3	Yes (2), HDCP2.2 Yes (1), HDCP1.3		Lock mode		Yes	Yes
	Digital	DP.	Yes (T), HDCPT.3	Yes (1), HDCP1.3		Content Rotation	1	Yes	Yes
		DVI-D	No	No		Gapless Playback		Yes	Yes
		HDBaseT	Yes	Yes		Tile Mode Setting	~	Yes (Max.15x15)	Yes (Max.15x15)
INPUT	Analog RGB Audio In External RS232C IN		No	No		Catting Date Clar			
			No	No		Setting Data Clor		Yes	Yes
			Yes	Yes		Firmware Update by Network		Yes	Yes
	Control	RJ45(LAN)	Yes	Yes		SNMP		Yes	Yes
	USB		Yes (2), USB2.0	Yes (2), USB2.0		ISM Mode		V	V
		peaker Out	Yes (1, L/R)	Yes (1, L/R)		(Image Sticking N	/linimization)	Yes	Yes
OUTPUT	External	RS232C OUT	Yes (1)	Yes (1)	SOFTWARE	Auto Set ID	AIII III III ZGCIOITI	Yes	Yes
OUTPUT		R3Z3ZC UUT		Yes (1), HDBaseT	SUFTWARE	Ctatus Mailine		Yes	Yes
	Control	RJ45(LAN)	Yes (1), HDBaseT			Status Mailing		TES	162
		Depth	5 mm	5 mm		"Outdoor API con		Yes	Yes
		Degree of Protection Tempered Anti-Reflective	IK10	IK10		(Backlight, Fan, Ill	luminance,		
			IKTO		Humidity, Door, cl	heck screen,	ies	les	
	Protection		Yes	Yes		rotation)"			
	Glass		Yes	Yes		Control Manager		Yes	Yes
	01033					3rd Party Control	l Crestron		
		Posistance (IP)	Yes Yes Yes		Compatibility	Connected	No	No	
		Resistance (IR) Shatter-Proof		Yes		Compatibility		V	V
MECHANICAL	ISHALLEI-FIUUI						DPM	Yes	Yes
SPECIFICATION	Bezel Color		Black	Black			On/Off	Yes	Yes
	Bezel Width Monitor Dimension (W x H x D) Handle VESA TM Standard						Schedule	103	103
			38.4mm(T/B), 26.0mm(L/R)	38.4mm(T/B), 26.0mm(L/R)			Holiday	V	V
			29" x 50.9" x 3.1" /	25.011 45.411 2.511 /	01 45 41 2 51 /	Power Mgmt.	Schedule	Yes	Yes
			737.4 x 1,292.5 x 88.0mm No	25.8" x 45.4" x 3.5" / 656.2 x 1153x 88.0mm No			Power on		
							Status	Yes (Standby, Power On, Last Status)	Yes (Standby, Power On, Last Status)
									Yes
				No (non standard)			Energy Saving	Yes	res
	Mount Interface		No (non-standard)	No (non-standard)			Smart Energy	Yes	Yes
	Internal Memory		16GB (System 4GB + Available 12GB)	16GB (System 4GB + Available 12GB)			Saving PM mode Wake on LAN		
			100b (System 40b + Available 120b)	10GB (System 4GB + Available 12GB)			PM mode	Yes	Yes
			No	No			Wake on LAN	Yes	Yes
	Wi-Fi						Power on Delay	Yes	Yes
		Dongle ready	No	No		D. Italia Co. ta T			
		Temperature	V (D 15 . 14(D 11614 1 :1)	V (D 15 : 84(D 11684 1 :11)		Daylight Saving T	ime	Yes	Yes
		Sensor	Yes (Panel Front, M/Board, LCM , Inside)	Yes (Panel Front, M/Board, LCM , Inside)		Beacon		Yes	Yes
		Auto Brightness sensor	Yes	Yes		HDMI-CEC			
	Sensors							Yes	Yes
						SI Server Setting		Yes	Yes
						HDbaseT		Yes	Yes
		BLU Sensor	Yes	Yes		WOL		Yes	Yes
		Pixel sensor	Yes	Yes		webRTC		Yes	Yes
			TES	TES	ENVIRONMENT	Operation Tempe	rature	-22°F to 122°F / -30°C to 50 °C	-22°F to 122°F / -30°C to 50 °C
HARDWARE		Proximity	No	No	CONDITIONS	Operation Humid	lity	5 % to 100 %	5 % to 100 %
		Sensor	Yes Yes	Yes Yes	SOUND	Speaker Safety		No	No
		Gyro Sensor							LII / aLII / CD
		Humidity						UL / cUL / CB	UL / cUL / CB
						IS EMC ErP / Energy Star SuperSign CMS		FCC Class "A" / CE / KCC	FCC Class "A" / CE / KCC
		Sensor						Yes / No	Yes / No
		Current Sensor	Yes	Yes				Yes	Yes
	Power Indicator		No	No					
					SOFTWARE	SuperSign Contro	ol/Control+	Yes/Yes	Yes/Yes
	Local Key Operation		No	No	COMPATIBILITY	SuperSign White	Palanco	No	No
	FAN		V (O I Cl I)	V (0 1 Cl 1)	CUIVIPATIBILITY	Supersign vvnice	Balance	INO	INO
			Yes (Open Loop , Closed Loop)	Yes (Open Loop , Closed Loop)		Signage 365 Care		Yes	Yes
	Dust / Water Proof		IP56	IP56		Signage 303 Care			
	Direct Sunlight		Yes	Yes				English, French, German, Spanish,	, Italian, Korean , Chinese(Simplified),
					LANGUAGE	Languages		Chinese(Original) Portugues(Brazil)	Swedish Finnish Norwegian Danish
	Power Supply		100-240V~, 50/60Hz	100-240V~, 50/60Hz		, ,		Russian, Japanese, Portugues(Eu	irope), Dutch, Czech, Greek, Persian
	Power Type		Built-In Power	Built-In Power		ъ .		Remote Controller Manual(FIG FSG) R	Regulation Book, Phone to RS232C Gender,
ELECTRICAL					ACCESSORIES &	Basic		LIDA	Al Cable
LLLCINICAL	DPM		1W	1W	OTHER				
			0.5\4/			Warranty		3 Year Limited	3 Year Limited
	Power off		0.5W	0.5W					
_									

