









## FEATURES

- Bodaciously Bright, with Wide Viewing Angle
- Extemely Durable
- Available in 12V or 24V
- IP68 Waterproof with Molded Power Wire
- 50,000 Hours Expected Lifetime
- 9ft Black Insulated Power Wire
- Available in 1ft, 2ft, 4ft, 6ft, 8ft, 10ft, 12ft, 14ft, 16ft, 20ft, 24ft, and 26ft Sections. Custom Lengths also Available
- Cuttable in Segments Includes (2) End Caps
- VHF and AIS Safe
- UL Rated (Rating is Lost if Cut or Modified) and RoHS
- Recommended Installation is 100% Silicone Adhered



















	Part #	LED Color	Length (ft)	Raw LM/m*	Power/16ft	Volts	Amps/ft	λ/ΤСС
6	FLS-CW-68-(LENGTH)	6000K (COOL WHITE)	UP TO 34'	2,400LM/m	72W	12V/24V DC	0.32A @ 12.9V DC	60PCS
	FLS-NW-68-(LENGTH)	3000K (WARM WHITE)	UP TO 34'	2,400LM/m	72W	12V/24V DC	0.275A @12.9V DC	60PCS
	FLS-RED-68-(LENGTH)	RED	UP TO 16'	1,285LM/m	72W	12V DC	0.275A @12.9V DC	60PCS
	FLS-GR-68-(LENGTH)	GREEN	UP TO 16'	1,740LM/m	72W	12V DC	0.275A @12.9V DC	60PCS
	FLS-BL-68-(LENGTH)	BLUE	UP TO 24'	1,320LM/m	72W	12V DC	0.275A @12.9V DC	60PCS
	FLS-RGB-68-(LENGTH)	RGB	UP TO 34'	1,910LM/m	85W	12V/24V DC	0.41A @12.9V DC	60PCS
Ŏ.	FLS-RGBW-68-(LENGTH)	RGBW	UP TO 34'	2,245LM/m	72W	12V/24V DC	0.32A @ 12.9V DC	60PCS
<b>1</b>	FLS-BL/CW-68-(LENGTH)	BLUE + COOL WHITE	UP TO 26'	665/1,200LM/m	72W	12V DC	0.275A @12.9V DC	30PCS
	FLS-BLKUV-68-(LENGTH)	UV BLACK LIGHT	UP TO 16'	400NM	72W	12V DC	0.275A @12.9V DC	60PCS











\* Based on LED manufacturer specifications

