



General Data	
Item No.	HR-112
Power	1.5 watts +10%
LED type	1 PC 1W CREE XPE LED
Luminous flux	76~95 lm
CCT	2700K,3000K, 4000K, 5000K,6000K
CRI	80+
Beam angle	30°x60°(Tilt x Pan)
Dimension	1.10" X 1.06" Diameter x Height
Cut out	27
Net weight	0.11 Lbs
Warranty	3 years
Certifications	CE, RoHS
Electrical Data	
Input voltage	DC12V / DC24V
Insulation class	Class III
Cable	1PC teflon cable 0.25M 2*0.3mm square
Driver	low voltage constant current output,excluding the transformer

Construction Data	
IP rating	IP67 Waterproof
IK rating	IK06
Housing	Stainless steel 316
Protection finishing	Stainless steel 316
Trim	Stainless steel 316
Glass	/
Loading capacity	242.5 Lbs
Cable Gland	/
Gasket	O-ring PMQ silicone seal
Accessories	
Spring	PC spring for recessed installation
Clip	SS304 clip for taking off the fixture from the handrail
Packaging	
Inner box size	2.36"x2.36"x1.57"
Carton size	32.5*26*22 cm (100PCS / carton)

SSS 316

3 Years Warranty

Photometric Data (3000K, 30°x60°)

