

KEEPING YOU IN CHARGE



PSC-61000A-C 6V 1A

Sealed Lead Acid Battery Charger A-C Battery Charger Series

FEATURES

- Universal input voltage range 10VAC 240VAC
- Automatic, current sensing dual-rate charging for efficient, care-free and safe operation
- LED indicators
- Alligator clip connectors with insulated sleeves


APPROVALS

- Approved for transport by air. D.O.T., I.A.T.A., F.A.A. and C.A.B. certified
- ETL • DOE
- FCC

• CE

 ISO9001:2015 – Quality management systems

CHARGER CHARACTERISTICS



GLOBAL HEADQUARTERS (USA AND INTERNATIONAL EXCLUDING EMEA)

Power-Sonic Corporation 365 Cabela Dr Suite 300, Reno, Nevada 89523 USA T: +1 619 661 2020 E: customer-service@power-sonic.com POWER-SONIC EMEA (EMEA – EUROPE, MIDDLE EAST AND AFRICA)

Smitspol 4, 3861 RS Nijkerk, The Netherlands T NL: + 31 33 7410 700 T UK: + 44 1268 560 686 T FR: + 33 344 32 18 17 E: salesEMEA@power-sonic.com

To ensure safe and efficient operation always refer to the latest edition of our Technical Manual, as published on our website. © 2019. Power-Sonic Corporation. All rights reserved. All trademarks are the property of their respective owners. All data subject to change without notice. E&O.E

PERFORMANCE SPECIFICATIONS

| Input Specs | |
|---|---------------------------|
| AC input voltage rating | 100Vac-240Vac |
| AC input frequency | 47Hz-63Hz |
| AC input current | 0.16A@115Vac/0.11A@230Vac |
| AC input power | 13.5W |
| AC static state current | 30mA |
| Output Specs | |
| Output voltage range | 5-7.5Vdc |
| Output current | 1A-6Vdc |
| Output power | 7.8W |
| Bulk charge current rating | 1A |
| Bulk charge voltage rating | 7.35Vdc |
| Float charge voltage rating | 6.7Vdc |
| Light switching current | 250mA |
| Charging capacity range | 5Ah to 12Ah |
| General Specs | |
| Efficiency | 0.58 |
| Over load protection | <1.5A |
| Short circuit protection | Yes |
| Reversed polarity connectors protection | Yes |
| Operating temperature | 0°C-40°C |
| Storage temperature | -30°C-85°C |
| Net weight | 90g |
| Dimensions | 80*50*57mm |
| Enclosure | Plastic Case |
| Application | Indoor |
| Charger type | Wall mounting |
| Plug type | Туре А (NEMA 1 - 15) |
| Safety Specs | |
| Withstand voltage (Hi-Pot) | 3000Vac ≤ 10mA (60s) |
| Insulation resistance | >100MΩ @500Vdc |
| Safety standard | ETL |
| Compliance | FCC |
| LED Indicator Status | |
| Green LED on | No load or float charge |
| Red LED on | Fast charge |

POWERPSSONIC

KEEPING YOU

FURTHER INFORMATION

Please refer to our website **www.power-sonic.com** for a complete range of useful downloads, such as product catalogs, material safety data sheets (MSDS), ISO certification, etc.