

MultiRound HF Housing

MR500-SS



The MR500-SS holds 5 AquaMetix® 20" cartridges designed to offer a high flow solution for specific removals of challenging contaminants. Housing utilizes 1.5" Inlet & Outlet and features a swing bolt lid.

Tested for the reduction of Chloramine, Chlorine, Lead, and Mercury

Capacities:

- 35000 gallons Chloramine >99% (Non-detect)
- 40000 gallons Mercury >98%
- 35000 gallons Lead >99%
- 70000 gallons Chlorine >99% (Non-detect)

Built-In Pressure Gauge

Built-In Pressure Release

Will also reduce other contaminants not listed above



<p>Labels in diagram: CLAMP, GASKET, VENT, HEAD NUT, PLATE, SPRING, THREADED MOUNT ROD, FILTER, "V" ROD, DRAIN, INLET, OUTLET.</p> <p>Dimensions: Overall Height 32 1/2", Width 10", Inlet/Outlet height 7", Drain height 3".</p>	Material, Body & Caps	316 SS
	Material, Eye Bolts	304 SS
	O-Ring	Silicone
	Lid Closure Type	Band Clamp
	Inlet/Outlet (Slip Connection)	1.5"
	Overall Height	32.5"
	Width	10"
	Rated Flow	5/7 GPM
	Maximum Flow	20 GPM
	Maximum working pressure	90 PSI
	Maximum temperature (housing)	125° F
	Shipping Weight (Empty)	40 lbs
	Carton dimensions	37"x17"x17"
Filter Change Frequency	6-12 Months	

MultiRound HF Housing

MR700-SS



The MR700-SS holds 7 AquaMetix® 20" cartridges designed to offer a high flow solution for specific removals of challenging contaminants. Housing utilizes 1.5" Inlet & Outlet and features a band clamp lid.

Tested for the reduction of Chloramine, Chlorine, Lead, and Mercury

Capacities:

- 49000 gallons Chloramine >99% (Non-detect)
- 56000 gallons Mercury >98%
- 49000 gallons Lead >99%
- 98000 gallons Chlorine >99% (Non-detect)

Built-In Pressure Gauge

Built-In Pressure Release

Will also reduce other contaminants not listed above



	Material, Body & Caps	316 SS
	Material, Eye Bolts	304 SS
	O-Ring	Silicone
	Lid Closure Type	Band Clamp
	Inlet/Outlet (Slip Connection)	1.5"
	Overall Height	32.5"
	Width	12"
	Rated Flow	7/10 GPM
	Maximum Flow	28 GPM
	Maximum working pressure	90 PSI
	Maximum temperature (housing)	125° F
	Shipping Weight (Empty)	55 lbs
	Carton dimensions	37"x17"x17"
Filter Change Frequency	6-12 Months	