



## LED LIGHT BAR BRACKETS - INSTALLATION INSTRUCTIONS

The Motobilt, Inc. LED Light Bar Brackets are designed to fit led light bars with different mounting widths. This is important because there are other name brand 50" led light bars that have a different mounting width. The 50-1/4" mounting width is noted on the website in the product description.

We do accept returns. You must contact us within 14 business days to let us know you want to return the item. The item must be in new condition. No modifications such as painting, sanding, cutting, grinding on and so on will be accepted. Returns may be subject to a 15% restocking fee and shipping charges may not be refunded. Please call the shop at 334-219-2333 or email [info@motobilt.com](mailto:info@motobilt.com)

### INSTALLATION:

Remove the factory bolts from one side of your windshield frame. Install the light bar bracket, but DO NOT tighten the bolts at this time. Finger tight to slightly loose is best. Repeat on the opposite side. Have a friend help install the light bar to the brackets and finger tighten the bolts. Once the light bar is in open position, tighten the light bar brackets to the windshield frame. Pay attention to alignment to the side of the windshield frame while you tighten the bolts. Aim the light bar and tighten to the light bar brackets.

The TJ and JK versions of the LED light bar brackets allow the wiring to go behind the bracket and come out towards the bottom. On these two Jeep models, the cowl under the windshield wipers can be removed to allow routing the wire hidden from

view. On the Jeep YJ, there is no removable cowl and no room to route the wires behind the brackets.

Routing the wires and connecting the light bar is left up to the customer.

[www.motobilt.com](http://www.motobilt.com)

334-219-2333