

COLORS:	<b>AMPOLA*</b> <b>BELVISO*</b> <b>BOLSENA*</b> <b>COMO*</b>	<b>DEVERO*</b> <b>MORO*</b> <b>VICO*</b>
	*AVAILABLE IN HERRINGBONE OPTION	
DIMENSIONS:	PLANK: 9/16" X 7" X 23"-69" (50% FULL) HERRINGBONE: 9/16" X 4-3/8" X 26"	
SPECIES:	EUROPEAN OAK	
FINISH:	UV URETHANE FINISH	
GLOSS LEVEL:	ULTRA-MATTE	
GRADE:	RUSTIC	
TREATMENT:	SMOKED: <b>AMPOLA, MORO, VICO</b> CARBONIZED: <b>BELVISO</b> NATURAL (NOT SMOKED OR CARBONIZED): <b>BOLSENA, COMO, DEVERO, MORO</b>	
TEXTURE:	WIRE BRUSHED	
EDGES:	MICRO-BEVELED	
TOP LAYER:	DRY-SAWN, 3MM THICK	
CORE:	HARDWOOD PLYWOOD	
PROFILING:	TONGUE & GROOVE FOUR SIDES (END-MATCHED)	
ADHESIVE:	TOP LAYER LAMINATION: EPI, FORMALDEHYDE-FREE PLYWOOD: PHENOLIC, EXTERIOR GRADE PRODUCT CONTAINS NO ADDED UREA-FORMALDEHYDE (NAUF) CARB ATCM PHASE II / EPA TSCA COMPLIANT (<0.05PPM)	
FSC-CERTIFIED:	NOT AVAILABLE	
WARRANTIES:	STRUCTURAL – LIFETIME FINISH – 25-YR RESIDENTIAL/3-YR LIGHT COMMERCIAL WHEN PROPERLY MAINTAINED PER CARE & MAINTENANCE INSTRUCTIONS APPROVED FOR USE OVER RADIANT HEAT SYSTEMS - REVIEW INSTALLATION INSTRUCTIONS THOROUGHLY FOR SYSTEM REQUIREMENTS BEFORE FINALIZING FLOORING SELECTION.	
INSTALLATION METHOD:	GLUE-DOWN, NAIL + GLUE, OR FLOAT	
CERTIFICATION:	FLOORSCORE CERTIFIED BY SCS GLOBAL SERVICES	