



## Prefinished Engineered Wood Flooring Product Specifications

<b>Color:</b>	EDMUND
<b>Collection:</b>	Dover
<b>Species:</b>	European Oak
<b>Finish:</b>	UV Urethane
<b>Gloss Level:</b>	Ultra-Matte
<b>Grade:</b>	Rustic
<b>Treatment:</b>	Reactive
<b>Texture:</b>	Smooth
<b>Edges:</b>	Micro-beveled
<b>Thickness:</b>	25/32"
<b>Plank Width:</b>	7-1/2"
<b>Length:</b>	96" (maximum one nested layer per carton, containing max two pieces @ minimum 2' length)
<b>Top Layer:</b>	Dry-sawn, 4mm thick
<b>Core:</b>	Hardwood Lumber (Hevea)
<b>Profiling:</b>	Tongue & Groove four sides (end-matched)
<b>Adhesive:</b>	EPI, formaldehyde-free Product contains No Added Formaldehyde (NAF, NAUF) CARB ATCM Phase II Compliant (<0.05PPM formaldehyde)
<b>FSC-certified:</b>	FSC available by special order
<b>Warranties:</b>	Structural – Lifetime Finish – 25-yr Residential/3-yr Light Commercial when properly maintained per Care & Maintenance Instructions Approved for use over radiant heat systems - review Installation Instructions thoroughly for system requirements before finalizing flooring selection.
<b>Installation Method:</b>	Nail-down, glue-down, or float
<b>Certification:</b>	Floorscore Certified by SCS Global Services

