

## **Product Specifications**

| Color:<br>Collection:<br>Species:<br>Finish:<br>Gloss Level:<br>Grade:<br>Treatment:<br>Texture:<br>Edges: | MONET<br>Tableau<br>European Oak<br>UV Urethane<br>Ultra-Matte<br>Rustic<br>Smoked<br>Wire Brushed<br>Micro-beveled   |
|--|---|
| Thickness:<br>Plank Width:<br>Length:  | 5/8"<br>8-5/8"<br>86-5/8" (min. 75% full length pieces, 2' min. length)   |
| Top Layer:<br>Core:<br>Profiling:  | Dry-sawn, 4mm thick<br>Hardwood Plywood<br>Tongue & Groove four sides (end-matched)   |
| Adhesive:  | Top layer lamination: EPI, formaldehyde-free<br>Plywood: Phenolic, exterior grade<br>Product contains No Added Urea Formaldehyde (NAUF)<br>CARB ATCM Phase II Compliant (<0.05PPM formaldehyde)               |
| FSC-certified:   | Not available   |
| Warranties:  | Structural – Lifetime<br>Finish – 25-yr Residential/3-yr Light Commercial when properly<br>maintained per Care & Maintenance Instructions<br>Not approved for use over radiant heat systems due to wide width |
| Installation Method:   | Nail-down, glue-down, or float  |
| Certification:   | Floorscore Certified by SCS Global Services   |

