



Prefinished Engineered Wood Flooring Product Specifications

| | |
|-----------------------------|---|
| Color: | BLEACHED TEAK |
| Collection: | True Teak |
| Species: | Teak |
| Finish: | UV Urethane |
| Gloss Level: | Ultra-Matte |
| Grade: | Light Rustic |
| Treatment: | Reactive |
| Texture: | Smooth |
| Edges: | Micro-beveled |
| Thickness: | 5/8" |
| Plank Width: | 7-1/4" |
| Length: | 23" – 82" |
| Top Layer: | Dry-sawn, 4mm thick |
| Core: | Solid Lumber Core, 100% Teak in all layers |
| Profiling: | Tongue & Groove four sides (end-matched) |
| Adhesive: | EPI, formaldehyde-free Product contains No Added Formaldehyde (NAF, NAUF) CARB ATCM Phase II Compliant (<0.05PPM formaldehyde) |
| FSC-certified: | Yes, FSC® 100% |
| Warranties: | Structural – Lifetime Finish – 25-yr Residential/3-yr Light Commercial when properly maintained per Care & Maintenance Instructions Approved for use over radiant heat systems - review Installation Instructions thoroughly for system requirements before finalizing flooring selection. |
| Installation Method: | Nail-down, glue-down, or float |



The mark of
responsible forestry