

# COMBICLICK® Fibre Discs

with Patented Cooling and Quick-Mounting System

## COMBICLICK® Fibre Discs Aluminium Oxide A-COOL



For general-purpose grinding, from coarse to ultra-fine, on poorly heat-conducting materials. Active additives in the coating ensure substantially increased stock removal while preventing loading and heat build-up in the workpiece.

For workpiece materials see the chart on page 3.

**Abrasive: Aluminium oxide A-COOL**

### Ordering note

Please order COMBICLICK® backing pad separately.

### Ordering example

CC-FS 115 A-COOL 60

### How to Order



CC-FS = COMBICLICK® fibre discs

115 = Dia. D mm

A = Abrasive aluminium oxide A

COOL = Bond

60 = Grit size

Order No.	Grit size							Dia. D [mm]	Max. speed [RPM]		
	50	60	80	120	150	180	220				
EAN 4007220											
CC-FS 115 A-COOL	-	722176	722190	722213	722220	-	722244	115	13.300	25	750
CC-FS 125 A-COOL	722251	722275	722299	722312	722329	722343	722367	125	12.200	25	875
CC-FS 180 A-COOL	722398	722411	722435	722459	722466	722527	722541	180	8.500	25	1850

## COMBICLICK® Fibre Discs Zirconia Alumina Z-COOL



For coarse but cool grinding at high stock removal rates. Zirconia alumina is a high-performance abrasive which delivers best results on powerful angle grinders at increased contact pressure. Active additives in the coating ensure notably improved stock removal while also preventing tool loading problems and reducing thermal loads on poorly heat-conducting materials.

For workpiece materials see the chart on page 3.

**Abrasive: Zirconia alumina Z-COOL**

### Ordering note

Please order COMBICLICK® backing pad separately.

### Ordering example

CC-FS 180 Z-COOL 60

### How to Order



CC-FS = COMBICLICK® fibre discs

180 = Dia. D mm

Z = Abrasive zirconia alumina Z

COOL = Bond

60 = Grit size

Order No.	Grit size				Dia. D [mm]	Max. speed [RPM]		
	36	50	60	80				
EAN 4007220								
CC-FS 125 Z-COOL	722763	722770	722787	722015	125	12.200	25	750
CC-FS 180 Z-COOL	722022	722046	722114	722053	180	8.500	25	1725

## COMBICLICK® Fibre Discs Ceramic Oxide CO-COOL



For aggressive grinding achieving maximum stock removal on hard, poorly heat conducting materials. Active additives in the coating ensure a substantially improved abrasive performance while preventing loading and reducing heat build-up in the workpiece. For workpiece materials see the chart on page 3.

**Abrasive: Ceramic oxide CO-COOL**

### Ordering note

Please order COMBICLICK® backing pad separately.

### Ordering example

CC-FS 180 CO-COOL 60

### How to Order



CC-FS = COMBICLICK® fibre discs

180 = Dia. D mm

CO = Abrasive ceramic oxide CO

COOL = Bond

60 = Grit size

Order No.	Grit size						Dia. D [mm]	Max. speed [RPM]		
	24	36	50	60	80	120				
EAN 4007220										
CC-FS 115 CO-COOL	763308	763315	763322	763339	763346	763353	115	13.300	25	750
CC-FS 125 CO-COOL	722442	722473	722480	722497	722503	722510	125	12.200	25	750
CC-FS 180 CO-COOL	722534	722558	722565	722589	722602	722626	180	8.500	25	1725