

 **Soudotec 390**

AC/DC+

**HARDFACING**

**DESCRIPTION**

All-position **economical hardfacing** electrode for hardfacing carbon steels, low-alloy steels, cast steels and manganese steels subjected to **abrasion, moderate impacts, and metal-to-metal friction.**

**CHARACTERISTICS**

- Excellent all-position weldability, even on AC power supply
- Crack-free deposit
- Smooth arc and low spatter
- Dense and porosity-free deposits
- Easy slag removal

Deposit rating scale

ABRASION										
IMPACT										
CORROSION										
METAL-METAL										
	1	2	3	4	5	6	7	8	9	10

Hardness (as-welded): 55 - 60 HRC  
 Deposit thickness: 3 passes maximum

**TYPICAL APPLICATIONS**

Crusher jaws, plow blades, excavation equipment, pulleys, guides and transport rails, chisels, scrapers, bucket teeth, etc.

**PROCEDURE**

Remove any trace of oil, grease and/or dirt from the surface. Remove damaged metal with **Soudotec 212 SP** or **Soudotec G12**. Keep a short arc with the electrode slightly inclined. Remove slag between passes. If more than three passes are required, use **Soudotec 340** or **Soudotec 342** as a cushion.

**MECHANICAL PROPERTIES**

Diameter: 5.0 mm (3/16") 4.0 mm (5/32") 3.2 mm (1/8") 2.5 mm (3/32")  
 Amperage: 180 - 230 A 140 - 175 A 110 - 135 A 65 - 100 A

Also available in flux-cored wire: **Soudotec FC 8332W** and solid MIG wire: **Soudotec M600**

Rev. : 7\_01

*Specialized welding alloys and technology. For technical assistance or for ordering:*



info@fsh-welding.ca  
 www.fsh-welding.ca

2341, 46<sup>e</sup> avenue  
 Lachine (Mtl), Québec  
 Canada H8T 3C9

Tél : 514.631.7670  
 1.800.361.9097  
 Fax : 514.636.3339