



EXTREME® SELF LIGHTING REPLACEMENT TIPS

Increase the range of your torch kit with additional self lighting tips. All TurboTorch® tips feature an orifice screw that can be easily removed for simple cleaning or replacement, extending the life of the tip.



PL-3A
Replacement Tip
Part No. 0386-0874



PL-5A
Replacement Tip
Part No. 0386-0818



PL-8A
Replacement Tip
Part No. 0386-0819



PL-12A
Replacement Tip
Part No. 0386-0820

AIR ACETYLENE



3A-TE
Replacement Tip End
Part No. 0386-1059



5A-TE
Replacement Tip End
Part No. 0386-1064



8A-TE
Replacement Tip End
Part No. 0386-1065



12A-TE
Replacement Tip End
Part No. 0386-1066

Tip No.	Tip Part No.	Tip Size	Soft Solders	Silver Brazes	Gas Flow		Replacement Orifice	Replacement Tip End	BTU
					@14 PSI SCFH	(0.9 BAR) M3/HR			
PL-3A	0386-0874	3/16" (4.8 mm)	1/4" – 1" (6.4 – 25 mm)	1/8" – 1/2" (3.2 – 13 mm)	3.6	0.108	OR-A3 0386-1001	3A-TE 0386-1059	1,280
PL-5A	0386-0818	1/4" (6.4 mm)	3/4" – 1 1/2" (19 – 38 mm)	1/4" – 3/4" (6.4 – 9.5 mm)	5	0.15	OR-A8 0386-1003	5A-TE 0386-1064	2,080
PL-8A	0386-0819	5/16" (7.9 mm)	1" – 2" (25 – 50 mm)	1/2" – 1" (13 – 25 mm)	7	0.21	– 0305-0511	8A-TE 0386-1065	2,520
PL-12A	0386-0820	3/8" (9.5 mm)	2" – 4" (50 – 102 mm)	1" – 2" (25 – 50 mm)	9	0.27	OR-T-6 0386-1024	12A-TE 0386-1066	3,360