



## JME ShortSlugger II

# Endurance magnetic base drill up to 1-1/4 in [32 mm]

Small, extremely lightweight 1-speed Endurance magnetic core drill with basic functionality for core drilling on the construction site.

Product number: 7 270 94 61 09 0

#### **Details**

- > For tough use, thanks to high-quality workmanship and internal motor cable routing.
- > Uncompromising service life through extradurable gearbox design with up to 400 hours of operation time.
- > Lightweight with FEIN high-performance motor and high torque for all core drilling work.
- > Excellent price / performance ratio.
- > Easy to read convenient magnetic holding force display.

- > Motion sensor.
- > Internal cooling.
- > High magnetic holding force.
- > Hand feed wheel can be mounted on either side.
- > Good accessibility in cramped operating situations.
- > Personal safety switches.

#### Price includes

- 1 coolant tank
- 1 chip hook
- 1 centering pin dia. 1/4 x 4 [6.35 x 100] in[mm]
- 1 chip guard
- 🖊 1 case

- 1 safety strap
- 1 centering pin dia. 1/4 x 3-1/8 [6.35 x 80] in[mm]
- 1 centering pin dia. 3/16 x 4 [4.75 x 100] in[mm]
- ✓ 1 allen key 5 mm

#### Product feature

- Magnet holding force display
- Hand feed wheel can be mounted on either side
- Tilt sensor



### **Application**

Mag base drilling metal up to 1-3/8 in dia.

Performing overhead work

★★

Installation work ★★

Workshop jobs ★★

★ suitable

★★ well suitable

#### Technical data

#### TECHNICAL DATA

Power consumption	1,200 W
Power output	770 W
Full load speed	450 rpm
No load speed	700 rpm

Carbide cutter max. dia.

1-1/4 [32] in[mm]

HSS cutter max. dia.

1-1/4 [32] in[mm]

Cutter max. drilling depth 2 [50] in[mm]

Cutter holder 3/4" Weldon

Stroke 3-9/16 [90] in[mm]

Magnetic holding force 2248 [10,000] lbs[N]

Magnetic base dimensions 6-7/8 [175] x 3-1/8 [80] in[mm]

Cable with plug 9.8 [3] ft[m]

Weight 23.81 [10.80] lbs[kg]



# Application examples





