



## Geberit Duofix frame for washbasin, 112–130 cm, wall-mounted tap, concealed



### Application purposes

- For drywall construction
- For installation in part- or room-height prewall installations
- For installation in room-height installation walls
- For installation in part- or room-height Geberit Duofix system walls
- For installation of washbasins
- For concealed taps
- For floor constructions 0–20 cm

### Characteristics

- Self-supporting frame, powder-coated
- Frame with  $\varnothing$  9 mm drilling holes for fastening in wood frame construction
- Galvanized feet

- Feet adjustable 0–20 cm
- Non-slip leg supports
- Rotatable foot plates
- Foot plate depth suitable for installation in U-profiles UW 50 and UW75 and Geberit Duofix system rails
- Fastening distance for washbasin 5–38 cm
- Mounting plate made of veneered wood, waterproof bonded
- Mounting plate adjustable in height and depth
- Fastening for connection bend, height-adjustable and sound-absorbing

### Scope of delivery

- Connection bend made of PE-HD,  $\varnothing$  50 mm
- Seal  $\varnothing$  44 / 32 mm
- 2 threaded rods M10
- Fastening material

### Art. no.

111.493.00.1

### Accessories

- Geberit Duofix fastening for washbasins with fastening distance 38–58 cm
- Geberit Duofix set of wall anchors for single installation
- Geberit Duofix set of wall anchors for single and system installation
- Geberit Duofix foot fastener set on rear wall
- Geberit Duofix fastening set for stud clearance 50–57.5 cm
- Geberit Duofix foot extension set for floor construction 20–40 cm
- Geberit Duofix set of feet with large foot plate



- Any boarding must be fixed tight up against the face of the Duofix frame and screwed directly to the frame

Created with Geberit online product catalogue - 21/06/2018