

**Geberit urinal flush control with pneumatic flush actuation, flush plate type 30**



**Application purposes**

- For manual flush actuation of urinals
- For Geberit frames for urinal with front actuation
- For installation in installation sets for Geberit urinal flush controls (from year of manufacture 2009)

**Characteristics**

- Flush plate with securing bar
- Flush time setting with air nozzles (pneumatic)
- Low flush actuation force
- Short stroke movement
- Flush actuation when the actuator button is released
- Flush volume can be reduced to 0.5 l per flush with regulating screw of installation set

**Technical data**

Flow pressure	1-8 bar
Maximum test pressure, water	16 bar
Maximum test pressure, air / inert gas	3 bar
Relative humidity	< 100 %
Maximum operating temperature, water	30 °C
Actuation force	< 12 N
Flow rate at 1 bar without flow limiter	0.3 l/s
Flow rate at 1 bar with flow limiter	0.24 l/s
Calculated flow rate	0.3 l/s
Minimum flow pressure for calculated flow rate	1 bar
Flush time, adjustment range	4/8/12 s

**Scope of delivery**

- Flush plate type 30
- Pneumatic flush actuation, premounted on mounting frame
- Pneumatic valve
- Fastening material

Art. no.	Surface / colour	Material designation
116.017.KH.1	Plate and button: gloss chrome-plated Design stripes: matt chrome-plated	Plastic

Art. no.	Surface / colour	Material designation
116.017.KJ.1	Plate and button: white Design stripes: gloss chrome-plated	Plastic
116.017.KK.1	Plate and button: white Design stripes: gold-plated	Plastic
116.017.KL.1	Plate: white Button: matt chrome-plated	Plastic
116.017.KM.1	Plate and button: black Design stripes: gloss chrome-plated	Plastic
116.017.KN.1	Plate and button: matt chrome-plated Design stripes: gloss chrome-plated	Plastic



- 
- Can be operated with used water (rainwater) provided it is passed through a filter system first

Created with Geberit online product catalogue - 21/06/2018