


**Plan**

**14943000510 Shower curtain PLAN uni**

**PRODUCT**



**DRAWING**



**PRODUCT ATTRIBUTES**

100% trevira, 80g/m<sup>2</sup>, vertical seams reinforced for stainless steel eyelets  
Distance between eyelets appr. 200 mm  
Weighted seam 50 g per meter  
impregnated, fungicide, antibacterial, antistatic, washable at 30°, shrinkage appr. 1-2%  
tested acc. to OEKO-Tex Standard 100  
complete with white curtain rings

**SURFACE**

truffle/8 eyelets

**DIMENSION**

1800x1400 mm

**SPECIFICATIONS**

KEUCO shower curtain PLAN uni, 14943000110, 55-2/16" x 70-14/16", truffle, 8 eyelets  
100% trevira, 0.0165 lb/ft<sup>2</sup>, vertical seams reinforced for stainless steel eyelets, distance between eyelets approx. 7-7/8", weighted seam 1.76 oz per 39-3/8"  
impregnated, fungizid, antibacterial, anitstatic, washable at 30° C / 86° F, shrinckage appr. 1-2%, tested acc, to OEKO-Tex Standard 100  
complete with curtain rings, white

Information concerning the measurements:

All dimensions refer to the actual finish size,

In order for the shower curtain not to touch the bottom of the bath tub or the floor we recommend the following:

Distance between the floor and the bottom edge of the curtain appr. 1-3/16",

Distance between the centre of the curtain pole and the top edge of the curtain

appr. 1-9/16",

Please allow appr. 1,3 to 1,5 times curtain pole length when calculating the required width of the curtain,