

# Sensorflow 21 Compact Tubular 15cm Panel Spout Integral Sensor, Mains

## ILLUSTRATED

**A4846** Sensorflow 21 compact tubular panel mounted 150mm projection spout, anti splash or anti vandal laminar flow outlet, integral sensor, copper tube inlets, mains

## ILLUSTRATED PRODUCT DETAILS

### Weights

**A4846** 1.70 KG

### Finishes

**A4846**  Chrome (AA)

### Materials

**A4846** Chrome Plated Brass

### Flow rates



**A4846** 3.7 Litres per minute @ 3 bar pressure

## FINISH OPTIONS



### Special Notes

Designed to be supplied with pre-mixed water. Consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device see A5900. The downward pointing sensor is set to work in the normal handwashing position. This helps to eliminate false triggering from high visibility clothing associated with forward facing sensors, we also do not recommend the use of Chromium plated wastes. Automatically shuts off if sensor is obstructed for a maximum of 55 seconds. Mains powered transformer with option to use up to 5 link units per main unit or alternatively there are stand alone battery powered units. Flow rate regulated to 3.7 litres per minute.



## ACCREDITATIONS

**A4846(AA)**



121015

## FEATURES

