




## Geberit Xeno<sup>2</sup> illuminated mirror with direct and indirect lighting



Example image



### Characteristics

- LED lighting
- Direct and indirect lighting
- Heated rear to prevent mirror steaming up
- Touch-sensor switch
- Dimmable

### Technical data

Protection degree	IP44
Protection class	I
Nominal voltage	100-230 V AC
Mains frequency	50 / 60 Hz
Operating voltage	12 V DC
Output voltage	12 V DC
Product material	Glass
Energy efficiency class	A++
Light colour	4200 K

Art. no.	B	B1	H	T	Power consumption	Luminous flux	Luminous flux, indirect
500.521.00.1	60 cm	32.5 cm	71 cm	5.5 cm	47.5 W	1495 lm	1960 lm
500.522.00.1	90 cm	62.5 cm	71 cm	5.5 cm	72.7 W	2275 lm	1960 lm
500.519.00.1	120 cm	71.5 cm	71 cm	5.5 cm	87.2 W	3055 lm	2380 lm
500.203.00.1	140 cm	91.5 cm	71 cm	5.5 cm	98.6 W	3575 lm	2095 lm
500.204.00.1	160 cm	91.5 cm	71 cm	5.5 cm	108 W	2940 lm	2940 lm