
## RAINSHOWER F-SERIES 40 " AQUASYMPHONY Ceiling shower 6+ sprays with light

MODEL # 26373001









## Product Description:

RAINSHOWER F-SERIES 40" AQUASYMPHONY Ceiling shower 6+ sprays with light

## Standard Specification:

1016 mm x 762 mm x 145 mm

metal

minimum flow rate 25 I/min

min. recommended pressure 3.0 bar

1 x AquaCurtain

1 x Pure XL spray

1 x 2 cold mist spray

2 x GROHE PureRain spray 400 x 190 mm

2 x XL Waterfall (separately controlled)

 $1 \times 4$  Bokoma Spray with adjustment angle  $20^{\circ}$  and combinations

full spectrum LED: soft light with changing rainbow colours individually adjustable: permanent lighting with colour selection

power supply for light 12 V DC

CE approved

SpeedClean anti-limescale system

GROHE DreamSpray perfect spray pattern

**GROHE StarLight** finish

requires rough-in set (26 376 001), F-digital Deluxe base unit box (26 376 000), Bluetooth unit (36 371 000) and various cable connections – all to be ordered separately due to individualised installation

The ceiling construction must be appropriate for the static requirement of the product (total product weight > 70 kg). Ceiling shower has to be controlled by 8 outlets + 1 hand shower outlet and the performance of the waste must be of sufficient size (> 100 l/min). For detailed planning please see separate planning & installation guide before start.

recommendation: configuration with Grohtherm F or Grohtherm SmartControl

## Color:

□ 26373001 Chrome