





Product Description:

Rapid SL 3 in 1 set for WC

Standard Specification:

with flush cistern 6 - 3 I

1.0 m finished installation height

for on-the-wall installations or studded walls

Includes

Frame/cistern for wall hung pan

Noise protection set

Wall brackets for on-the-wall installation (38 558 00M)

Chrome flush plate

GROHE Fresh retrofit set:

enables access to concealed cistern

to add a cleaning tablet

(chlorine free tablets only)

Fixing bolts for wc and floor

Details:

200mm height adjustment, lockable when at required height

distance of fixing bolts 180/230 mm

outlet bend Ø 90 mm

depth adjustable

reducer Ø 90/110 mm

Insulated against condensation

flushing cistern 6 - 9 I

pneumatic discharge valve offering 2 modes of

operation: dual flush or single flush

front/top actuation

water supply from left/right or back

including integrated angle valve

and push fit flexible hose union

low noise (group I acc. to

German Noise Specification)

Insulated against condensation

Includes:

1/2" water supply connection including integrated angle valve and push fit flexible hose union protecting block

with wall brackets for on-the-wall installations Nova Cosmopolitan flush plate

horizontal installation

for horizontal installation only

chrome

for mounting of small flush plates please order inspection shaft 40 911 000 (sold separately)





GROHE StarLight chrome finish
GROHE EcoJoy technology for less water and perfect flow

Color: □ 118599