

DRAFT BREWER™ SNAP TAP

THE MOST PORTABLE AND PARTY-READY
WAY TO SHARE BEER ON TAP.

INSTALLING & USING THE SNAP TAP

1. Ensure your brew is well chilled and serving pressure is near 5 psi to avoid foaming.
2. Before attaching your Snap Tap to a keg, ensure the tap handle is pushed all the way back, or you may be surprised by a squirt of beer.
3. Attach the Snap Tap as you would a draft line. Pull the sliding portion of the black ball lock disconnect back, place the disconnect on the keg and push down until it clicks into place.
4. It is a good idea to keep a rag or paper towel beneath each keg with a Snap Tap attached, as there may be a few small drips between each pour. Alternatively, you can hold your cup to the faucet a little longer to catch those few drips.

CARE & MAINTENANCE

Whenever you are finished dispensing, rinse your Snap Tap in warm water. Open and close the faucet while rinsing to release any beer that may be left in the faucet. Allow to dry completely before storing.

CLEANING

For a deep clean, disassemble your Snap Tap and soak in a food-safe cleaning solution. Scrub with a sponge or cloth to remove any dried-on beer or debris. You can follow this by rinsing and soaking it in a sanitizer solution. Do not soak longer than a few hours.

ASSEMBLING YOUR SNAP TAP

Screw each piece on in the sequence depicted in the following diagram.
Ensure all pieces are securely tightened together.

