



**Heated incounter soup well**

- Capacity approximately 10 litres
- Thermostatically controlled by remote thermostat
- Supplied with lift out inner soup pot and hinged lid
- Option of lift out inner soup pot with two handles for easy movement between kitchen and servery, and lockable hinged lid
- Option of control panel back box to facilitate installation of control panel
- Includes drain kit which we strongly recommend be fitted.

<u>Product code</u>	<u>Description</u>	<u>Cutout diameter</u>	<u>Flange diameter</u>	<u>Build in height with drain kit</u>
08.2053V	Heated incounter soup well with drain kit. Complete with soup pot hinged lid with ladle notch.	280 mm	312 mm	304 mm
08.2053	Heated incounter soup well with drain kit. Complete with soup pot with handles and lockable hinged lid with ladle notch.	280 mm	312 mm	304 mm

**General specification** Heated incounter soup well with drain kit. Capacity approximately 10 litres. Thermostatically controlled by remote (up to 1500mm) thermostat, with on/off switch, mounted in control panel. Control panel cutout 148 high mm x 86 mm wide. Overall build-in depth (including drain valve) is 304mm x 312 mm diameter. Supplied with lift out soup pot and hinged lid with ladle notch. Fitted with cable and plug. Electric load of 350W. Operates from 230V - 50HZ - 1PH electric supply. Includes drain kit which we recommend be installed.