4-Wheel

Weight Capacity	400 lbs.
Maximum Speed ¹	Up to 7 mph
Ground Clearance ³	2" at motor
Turning Radius ³	43"
Overall Length ³	48"
Overall Width ³	24.25"
Seat-to-Ground Height	22.25"-24.25"
Seat-to-Deck Height	15.5"-17.5"
Seat Back Height	21"
Front Tires	9" solid
Rear Tires	10.75" solid
Suspension	Front and rear (CTS Suspension)
Range Per Charge ^{1,2}	Up to 18 miles at 400 lbs. Up to 24 miles at 200 lbs.
Total Weight Without Batteries ⁵	197.6 lbs.
Heaviest Piece When Disassembled ³	75 lbs. (front section)
Standard Seating ³	Type: Reclining High Back Weight: 45.8 lbs. Material: Black Vinyl Dimensions: Width: 20", Depth: 20"
Drive System	24-volt DC motor, rear-wheel drive, dual in-line
Dual Braking System	Regenerative and electromechanical
Battery Requirements ^{4,6}	Size: (2) 40 Ah Weight: 30.25 lbs. each
Battery Charger	Off-board, 3.5 amp
Warranty	Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited Battery: 6-months

- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.
- 2 Tested in accordance with ANSI/RESNA, MC Vol2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum
- 3 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
- 4 Battery weight may vary based on battery manufacturer.
- 5 Includes standard seat weight.
- 6 AGM or gel cell type required.



Beamsville, ON • 888-570-1113

pridemobility.ca D 1 5 6









HCPCS codes provided should not be considered as legal advice and do not guarantee reimbursement. DME providers are responsible for determining appropriate billing codes when submitting for insurance reimbursement.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or $-3\,\%$. Special order seats or non-standard dimensions will not be fold-flat and depth-adjustable.



CUTTING-EDGE VERSATILITY

THE FIRST 4-WHEEL INDOOR/OUTDOOR SCOOTER!





Ambient voltmeter

Standard large front basket

Full LED light package includes LED headlights and rear lights with sequential turn signals and puddle light under the tiller



Front LED lights



Pride's CTS Suspension



Pride's patent-pending, intelligent-turning, iTurn Technology™ provides 4-wheel stability with 3-wheel maneuverability

With contemporary styling and cutting-edge technology, the **Zero Turn 10** is the perfect combination of aggressive performance and maneuverability. Powerful dual motors and two-wheel drive offers aggressive traction, easily tackling rugged terrain on trails. When you're done spending time outdoors, the Zero Turn 10 transitions seamlessly indoors. Maneuver smoothly through the halls and doorways with iTurn TechnologyTM.

Additional Features

- Three-speed control lets you adjust your speed when moving from indoor to outdoor driving
- Delta tiller with wraparound handles
- Easy access tiller-mounted XLR charger port
- USB charger integrated in the tiller for convenient charging of smart phones and portable electronic devices
- Integrated storage/cup holder in the tiller

Available Colours







Pearl White

Ocean Blue**

Candy Apple Red

Accessories*

- Cane/crutch holder (single, double)
- Cell phone holder
- Cup holder
- Forearm crutch holder
- 50", 60", 70" lap belt
- Oxygen tank holder
- Quad cane holder
- Rear basket
- Rearview mirror
- Saddlebag
- Walker holder
- Weather cover
- Wishbone crutch holder

^{*}Only one rear accessory can be used at a time.

^{**}Matte finish