# SunDanzer

# HOUSEHOLD PRODUCTS

SunDanzer

2023

# SunDanzer

# Household Products







DC100



Model	Volume
DC100	100 LITERS
DC160	160 LITERS
DC400	400 LITERS
DCR450	450 LITERS

DCRF450

DC100 - SMALL BUT MIGHTY

## Highlights

- Optimized insulation thickness
- Side handles for easy handling
- Premium DC compressor
- Lightweight
- Handle with lock
- 2-year limited warranty







Specifications:

Internal Volume:	100 liters
Exterior Dimensions:	25.75 x 26.75 x 30.5in
Insulation Thickness:	60mm (2.4in)
Refrigerant Type:	R-600a
Refrigerator Temp Range	9 to -1°C (48 to 30°F)
Freezer Temp Range:	-2 to -21°C (29 to -6°F)
Voltage Range:	10-31VDC
Input Power:	35-65 Watts
Fuse Size:	12V:15A / 24V:7.5A
Refrigerator Energy use in	132°C: 0.220kWh/d
Freezer Energy use in 32°C	C: 0.440kWh/d
*Min System Refrigerator:	110W PV, 35Ah Battery
*Min System Freezer:	220W PV, 70Ah Battery
Defrost:	Manual
Units in a container (40' / 2	20'): 114 / <u>54</u>

# DC160- KING OF EFFICIENCY

### Highlights

- Class leading efficiency
- 3 baskets for organization
- Side handles for easy handling
- Premium DC compressor
- LED refrigerator light
- Handle with lock
- 2-year limited warranty





## Specifications:

•			
Internal Volume:	160 liters		
Exterior Dimensions:	37 x 26.25 x 34.25in		
Insulation Thickness:	110mm (4.33in)		
Refrigerant Type:	R-600a		
Refrigerator Temp Range	e: 9 to -1°C (48 to 30°F)		
Freezer Temp Range:	-2 to -21°C (29 to -6°F)		
Voltage Range:	10-31VDC or 40-75VDC		
Input Power:	35-65 Watts		
Fuse Size:	12V:15A / 24V:7.5A		
Refrigerator Energy use i	in 32°C: 0.168kWh/d		
Freezer Energy use in 32°	°C: 0.441kWh/d		
*Min System Refrigerator	r: 100W PV, 26Ah Battery		
*Min System Freezer:	220W PV, 70Ah Battery		
Defrost:	Manual		
Units in a container (40'	/ 20'): 72 / 36		
*Minimum sizing based on 100% DOD of the battery. Sizing			

## DC400 - BIGGER IS BETTER

## Highlights

- Sliding glass top cover
- 5 baskets for organization
- Heavy-duty locking bottom wheels
- Side handles for handling
- Premium DC Compressor
- LED refrigerator light
- Handle with lock
- 2-year limited warranty







Specifications:

Internal Volume:	400 liters	
Exterior Dimensions:	63.5 x 28.75 x 34.25in	
Insulation Thickness:	80mm (3.15in)	
Refrigerant Type:	R-290	
Refrigerator Temp Range	e: 9 to -1°C (48 to 30°F)	
Freezer Temp Range:	-2 to -21°C (29 to -6°F)	
Voltage Range:	10-31VDC or 40-75VDC	
Input Power:	60-110Watts	
Fuse Size:	12V:30A / 24V:15A	
Refrigerator Energy use i	n 32°C: 0.450kWh/d	
Freezer Energy use in 32°	°C: 0.800kWh/d	
*Min System Refrigerator: 225W PV, 70Ah Battery		
*Min System Freezer:	400W PV, 125Ah Battery	
Defrost:	Manual	
Units in a container (40' /	<sup>'</sup> 20'): 48 / 24	
*Minimum sizing based on 100% DOD of the battery. Sizing		

DCRF450- DUAL PERSONALITY

### Highlights

- 50% thicker insulation than standard
- Double gasket freezer door
- Premium DC Compressor
- LED refrigerator light
- Three adjustable shelves
- One Lower Basket
- Doors hinges can be left or right handed
- 2-year limited warranty





### Specifications:

•	
Internal Volume Refrigerato	or: 283 liters
Internal Volume Freezer	142 liters
Exterior Dimensions:	30.75 x 28.5 x 74.75
Insulation Thickness:	Variable
Refrigerant Type:	R-290
Refrigerator Temp Range:	7 to 0°C (44 to 32°F)
Freezer Temp Range:	-10 to -14°C (14 to 7F)
Voltage Range: 1	0-31VDC or 40-75VDC
Input Power:	60-110Watts
Fuse Size:	12V:30A / 24V:15A
Energy use in 32°C:	0.890 kWh/d
*Min System Size:	445W PV, 140Ah
Defrost:	Manual
Units in a container (40' / 20	)'): 42 / 20



# CONTACT US FOR INQUIRIES

#### **ADDRESS**

420 E Aviation Drive Suite #130 Tucson, AZ, 85714

#### **EMAIL**

info@sundanzer.com

#### PHONE

(520)882-9100

