

SPECIFICATION SHEET

Product 5MP Fixed 4.0mm Outdoor IR IP CCTV Camera Mini Bullet WDR

Model Number EZC 51FMB 4.0

Image Sensor 1/2.9" progressive scan CMOS

Min. illumination 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR

Shutter time 1/3s ~ 1/100,000s

Lens 4mm @ F2.0 (2.8mm optional)
Angle of view: 63.5° (81° for 2.8mm)

Day & night IR cut filter with auto switch

Digital noise reduction 3D DNR

Wide dynamic range 120dB WDR

Video compression H.265 / H.264 / MJPEG

Max. Image Resolution 2560 x 1920

Frame rate 20fps (2560×1920), 30fps(2560×1440, 2048×1536, 1920×1080, 1280×720)

Image settings Saturation, brightness, contrast, sharpness adjustable through client software or web browser

Network storage Support microSD/SDHC/SDXC card (128Gb) local storage, NAS (NFS,SMB/CIFS), ANR

Alarm trigger motion detection, tampering alarm, network disconnect, IP address conflict, storage exception

Protocols TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos

Security User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark

Communication interface 1 RJ45 10M/ 100 M Ethernet interface

Operating conditions -30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 95% or less (non-condensing)

Power supply 12 VDC +/- 25%, PoE (802.3af)

Power consumption Max 6W, PoE(802.3af, class 3), 7W

Weather proof rating IP67

IR range UP to 100ft

Dimension Φ 2.76" × 6.1"

Weight 0.9lbs

Electrical Box EZA-280ZJ-XS

