

SUBMERSIBLE CLEAN WATER BRUSHLESS DC SOLAR PUMP



MODEL SPECIFICATIONS

MODEL NUMBER	PUMP						SOLAR PANEL		
	V	POWER (W)	MAX FLOW (M ³ /H)	MAX HEAD (M)	OUTLET SIZE	CABLE (M)	V	POWER (W)	QTY
TSG12/13-60/550	60	550	12	13	2"	15	30	250	3
TSG14/18-72/750	72	750	14	18	2"	15	30	250	4
TSG15/23-96/1000	96	1000	15	23	2"	15	30	250	5

MECHANICAL SPECIFICATIONS

Dimensions	2.00 m x 1.60 m x 1.85 m
Weight	75 kg
Mounting options	Floor

MATERIAL OF PUMP

Outlet	Iron
Pump head	Iron
Pump body	Iron
Impeller	Aluminium
Motor	Brushless DC motor
Warranty	12 months


LIST OF INCLUSIONS

SOLAIR BLDC CONTROLLER



- MPPT solar BLDC controller

SOLAR FRAME



- Single Pole
- Hot-dipped galvanized solar frame

SOLAR PANELS



- 4 x 250 W Solar Panels
- Polycrystalline

SUBMERSIBLE DIRTY WATER BRUSHLESS DC SOLAR PUMP



MODEL SPECIFICATIONS

PUMP							SOLAR PANEL		
MODEL NUMBER	V	POWER (W)	MAX FLOW (M ³ /H)	MAX HEAD (M)	OUTLET SIZE	CABLE (M)	V	POWER (W)	QTY
TSG40/10-72/1100	72	1100	40	10	3"	15	30	250	6
TSG45/12-96/1500	96	1500	45	12	3"	15	30	250	8
TSG48/10-96/1500	96	1500	48	10	4"	15	30	250	8
TSG56/14-280/2200	280	2200	56	14	4"	15	30	250	12

MECHANICAL SPECIFICATIONS

Dimensions	2.00 m x 1.60 m x 1.85 m
Weight	75 kg
Mounting options	Floor

MATERIAL OF PUMP

Outlet	Iron
Pump head	Iron
Pump body	Iron
Impeller	Aluminium
Motor	Brushless DC motor
Warranty	12 months


LIST OF INCLUSIONS

SOLAIR BLDC CONTROLLER



- MPPT solar BLDC controller

SOLAR FRAME



- Single Pole
- Hot-dipped galvanised solar frame

SOLAR PANELS



- 4 x 250 W Solar Panels
- Polycrystalline